SEPTEMBER 1983 U.S.F.S. LANDS (N 89°45'E 570.01') [N 88°39'40"E] FNO. 3/8"CAPPED \$N.89°51'13"E 2641.76'} C. OF 5. 244 125.24 442.09 [51.05'20"E 50'] - 3- 567.33' FOTAL N 89 47 19 E S 1º09'22"E - - (567.59) FND 16 CAPPED STEEL PIN BY MOL 4232 S 6.056 ACRES -BADLY BENT REMAINDER Em \( a = 27°59'39'\\ R = 550.9'\\\ L = 269.46'\\ 3.007 ACRES ! GROSS 3.007 TEASE 0.178 - NET EME 3.027 ACREST OCCASIONAL N10°25'31'W 9.26 SALE DETAIL (NOT TO SCALE) SCALE Troy, Montana Ninneman Engineering

JOB NO. 83-40 TUBE NO. 94

た。**g** Company of the Manager in th

LINCOLN COUNTY, MONTANA

# RTIFICATI DF BURTET

IN THE NE 1/4 OF SECTION 17, TWP. 30N., R. 29W., P.M.M.

#### DESCRIPTION OCCASIONAL SALE TRACT ="A"

An irregular tract of land near Libby, in Lincoln County, Montana, lying wholly within the NE's of Section 17, Township 30 North, Range 29 West, P.M.M., containing 3.027 acres, more or less, and more particularly described

Beginning at an uncapped 3/4 inch steel pin on the curved Southeasterly right-of-way line of an existing 60 foot wide public road where the radius bears S 44009'10"E; thence, along said line, along the arc of a curve to the left, having a radius of 523.05 feet, turning through an angle of 21050'50", a length of 199.44 feet to a 5/8 inch capped steel pin stamped JHN 4661S (hereinafter referred to as "a 5/8 inch pin"); thence, leaving said right-of-way line, S 56°25'24"E 512.23 feet to a 5/8 inch pin; thence, S 25°28'40"W 102.22 feet to a 5/8 inch pin; thence, S29° 58'40"W 204.31 feet to a 3/8 inch capped steel pin stamped W & R 4232S; thence, N 45018'20"W 554.52 feet to the point of beginning.

Subject to and including a ten foot wide water line easement, containing a het area of 0.141 acre, more or less, as shown hereon.

### DESCRIPTION REMAINDER= "B"

An irregular tract of land near Libby, in Lincoln County, Montana, lying wholly within the NE's of Section 17, Township 30 North, Range 29 West, P.M.M., containing 3.007 acres, more or less, and more particularly described as follows:

Beginning at a 5/8 inch capped steel pin stamped JHN 4661S (hereinafter referred to as "a 5/8 inch pin") on the Easterly right-of-way line of an existing 60 foot wide public road; thence, leaving said line, S 64000'17"E 547.74 feet to a 5/8 inch pin; thence, S 35<sup>0</sup>01'53"W 64.54 feet to a 5/8 inch pin; thence, S 25<sup>0</sup>28'40"W 222.00 feet to a 5/8 inch pin; thence, N 56°25'24"W 512.23 feet to a 5/8 inch pin on the curved southeasterly right-of-way line of said public road, where the radius bears S 66000'00"E; thence, along said line, along the arc of a curve to the left, having a radius of 523.05 feet, turning through an angle of 7°28'00", a length of 68.16 feet to a 5/8 inch pin; thence, N 16°32'00"E 152.45 feet to the point of beginning.

Subject to and including a ten foot wide water line easement, containing a net area of 0.113 acre, more or less, as shown hereon.

### EXEMPTION CERTIFICATE/PURPOSE FOR SURVEY

I hereby certify that the purpose for this division of land is to transfer ownership of the parcel created as an occasional sale, furthermore, I certify that I am entitled to use this exemption in that I am in compliance with all conditions imposed in the use of this exemption; therefore, this division of land is exempt from review as a subdivision pursuant to Section 76-3-207 (d), M.C.A.

Lewis Y. Blackwell Date

The foregoing certificate was subscribed and sworn to before me this 30 day of 160. 1983.

Notary Public Fesiding at My Commission Expires

## LEGEND

- ⑤ 5/8" X 24" capped steel pin stamped JHN 4661S
- O Found monument as noted
- · Point computed only, not found or set
- Record per C. of S. 463
- () Record per Plat No. 1280
- [] Record rotation as shown on C. of S. 463

APPROVED: APPROVED: ATTESTED: County Clerk and Recorder Dated this 12th day of Seconder 1950

COUNTY OF LINCOLN day of December 19 83 10:20 0 clock H. M Couply Clerk Jand Recorder Deputy

CERTIFICATE OF SURVEY NO. 1210