

CERTIFICATE OF SURVEY: RESURVEY OF A DIVORCED HIGHWAY PARCEL

In H.E.S. 845, Unsurveyed Sections 9 & 10, Twp. 34 N., R. 33 W., P.M.M.
For: Gary Thom & Eddie R. Markley
Date: March 2006

PURPOSE OF SURVEY

The purpose of this survey is to retrace an existing tract of record and that no new parcels have been created; therefore, this survey is exempt from review as a subdivision being completed pursuant to 76-3-404 M.C.A.

DESCRIPTION OF PARCEL A

A tract of land located in H.E.S. 845, in unsurveyed Sections 9 & 10, of Twp. 34 N., R. 33 W., P.M.M., containing 9.33 acres more or less and more particularly described as follows:

Beginning at a 5/8 inch dia. rebar capped K.E.D. 4975-S located on the west right of way of Yaak Highway No. 508, and bears N18°03'44"W 72.51 feet from a 3 1/4 inch dia. alum. monument which marks Corner No. 7 of H.E.S. 845; thence from the true point of beginning, N18°03'44"W 2235.26 feet along the west line of said H.E.S. 845, to a 5/8 inch dia. rebar capped K.E.D. 4975-S located on the west right of way of said Yaak Highway No. 508; thence along said right of way, S28°11'50"E 134.14 feet to a 1 1/2 inch dia. alum. MDOH right of way monument; thence, S32°45'15"E 153.43 feet to a 1 1/2 inch dia. alum. MDOH right of way monument; thence on the arc of a curve to the left, a distance of 209.36 feet, turning through a delta angle of 06°32'40", and having a radius of 1832.90 feet, to a 1 1/2 inch dia. alum. MDOH right of way monument; thence on the arc of a spiral curve to the left, having a chord bearing of S38°47'47"E 152.97 feet to a 1 1/2 inch dia. alum. MDOH right of way monument; thence, S48°56'30"E 123.43 feet to a computed point; thence on the arc of a spiral curve to the right, having a chord bearing of S38°26'30"E 146.87 feet to a computed point; thence on the arc of a curve to the right, a distance of 82.68 feet, turning through a delta angle of 04°05'50", and having a radius of 1156.23 feet, to a 1 1/2 inch dia. alum. MDOH right of way monument; thence, S17°42'10"E 97.08 feet to a 1 1/2 inch dia. alum. MDOH right of way monument; thence on the arc of a curve to the right a distance of 640.21 feet, turning through a delta angle of 32°17'00", and having a radius of 1136.23 feet to a 1 1/2 inch dia. alum. MDOH monument; thence on the arc of a spiral curve to the right, having a chord bearing of S07°28'08"W 145.62 feet to a computed point; thence, S08°38'19"W 75.40 feet to a computed point; thence on the arc of a spiral curve to the left, having a chord bearing of S07°22'12"W 154.55 feet, to a 1 1/2 inch dia. alum. MDOH monument; thence on the arc of a curve to the left, a distance of 236.01 feet, turning through a delta angle of 11°07'17", and having radius of 1215.90 feet, to the point of beginning.

The aforescribed Parcel A contains 9.33 acres more or less and is subject to and together with all appurtenant easements of record.

CERTIFICATE OF SURVEYOR STATE OF MONTANA County of Lincoln

I, Kenneth E. Davis, a registered land surveyor do hereby certify that I have performed the survey shown on the attached Plat or that such a survey was performed under my supervision to my best knowledge and ability; that said survey is true and complete as shown and the monuments found and set occupy the position shown hereon.

Dated this 5th day of May, 2006 A.D.
Kenneth E. Davis
Kenneth E. Davis Registered Land Surveyor No. 4975-S

EXAMINED AND APPROVED FOR LINCOLN COUNTY BY:

Approved this 26 day of April, 2006 A.D.
[Signature]
Montana Examining Land Surveyor Registration No. 14731 PLS

STATE OF MONTANA
County of Lincoln

Filed on this 9th day of May, 2006 A.D. at 9:30 O'clock A.m.

[Signature]
County Clerk and Recorder
[Signature]
Deputy



H.E.S. 845 COR. #1
1925.35'
N29°11'49"W
H.E.S. 845 COR. #8
COMPUTED PER BROKEN BOUNDARY PROPORTION

S28°11'50"E
134.14'

GRUBSTAKE SUBDIVISION

Δ = 06°32'40"
R = 1832.90'
L = 209.36'

SP CHORD
S38°47'47"E
152.97'

S48°56'30"E
123.43'

SP CHORD
S38°26'30"E
146.87'

9.33 ACRES ±
PARCEL A
U.S.F.S.
N18°03'44"W
2235.26'

04°05'50"
1156.23'

02.68'

Δ = 32°17'00"
R = 1136.23'
L = 640.21'

SP CHORD
S07°28'08"W
145.62'

S08°38'19"W
75.40'

SP CHORD
S07°22'12"W
154.55'

Δ = 11°07'17"
R = 1215.90'
L = 236.01'

S07°28'08"E
398.63'
(6.04 CH)

H.E.S. 845 COR. #6

H.E.S. 845 COR. #7

P.O.B.
N18°03'44"W
72.51'

H.E.S. 845 COR. #7

YAAK HIGHWAY NO. 508
(DIVORCED PARCEL)
C.O.S. 2693-S


BURNT DUTCH

LOT 1 POVERTY ACRES

LOT 2 POVERTY ACRES

Legend

- ◆ SET A 5/8 BY 30 INCH LONG REBAR WITH A 1 1/4 INCH DIA. PLASTIC CAP STAMPED K.E.D. 4975-S
- FOUND 5/8 INCH DIA. REBAR CAPPED K.E.D. 4975-S
- FOUND H.E.S. CORNERS AS NOTED
- FOUND 1 1/2 INCH DIA. ALUM. MDOH MONUMENT
- COMPUTED POINTS
- () RECORD PER POVERTY ACRES



Graphic Scale:



(1 inch = 200 ft.)

Davis Surveying Inc.
TROY MONTANA, (406)295-5441

DATE: 1/07/05
Land Projects 2005
DRAWN BY: C.JR.
FILE: T303103.dwg

Doc # 193906 CERTIFICATE OF SURVEY NO. 3524