	ERTIFIED CORNER RE 256 S4 _{T.} 25 N. _{R.} 28		Lincoln	_County	
I. <u>Record:</u> NoneII. <u>Found:</u> No record r	monuments found.				
steel reb	he corner point, determined by ar 30 ins. long, 29 ins. in the	ground, with a 3			
	n cap marked as shown below diam., bears N36°E, 14.10 ft. d		SE 1/256 S4	4 BT.	
A Larch, 10 in	A Larch, 10 ins. diam., bears S5°W, 12.90 ft. dist., scribed CSSWSE 1/256 S4 BT.				
Painted faces and 6 in. wide red bands to all bearing trees and attached Land Survey Monument and Bearing Tree signs.					
	s on line 1.75 ft. East and 1.7 by Monument and Property Line		monument	with	
Magnetic declin	ation: 18° East				
Equipment used	d: Hand compass and loggers	tape			
	of Survey No. 4121 Lincoln s for additional survey informa	T25N R S4 CSSW 1/25 7322 201 ation.	/SE 6 LS		
Kootenai Surveyors Inc	., 314 California Av., Libby, MT	T. 59923 (406) 29	3-4354		
PCTC Upper McGinnis 2011 10" Larch SKETC	H OF CORNER	Relly Received the information of the information o	re Ground Party Chie re Ground Party Chie r Record conjectty in Act (70–22–10)	epresents work compliance with desc. 7322	
Office of Clerk and Recorder, Co	Lincoln	"corner			
record" was filed for record on was noted on the cross—indebook No.	236201 BOOK: CCR CCER'S STATE OF MONTANA LINCOLN COUNTY RECORDED: 12/01/2011 2:20 KOI: TAMMY D. LAUER CLERK AND RECORD FEE: \$0.00 BY TO: KOOTEMAI SURVEYORS INC. P.O.BOX	er Leany Of	Sec 1	. 4	
Cross Index No					
Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors • corner this sheet					