corners.

3. Description of monume—and accessories set to perpetuate the corner position.

4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner macking, topography ties, position of accessories, etc.


5. Ceritheatton must be signed and sealed by Registered Land Surveyor in State of Montana.

6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

orner East corner Section 2 T. 25N R. 29W P.M.M. Lincoln County

- 1. 39.35 chains (resurvey): Set a granite stone, 12 X 8 X 6 inches, 8 inches in the ground for 4 Section corner for Section 2 only, marked 4 on the W. face, from which a Fir 5 inches in diameter, bears S 56 W., 31 links distance, marked 4S 2 B.T. A Fir, 8 inches in diameter, bears N 86 W 11 links distance, marked 4S 2 B.T.
- 2. Found: BLM brass capped monument from which an 8" Fir bears S 56°W 20.5 feet S2 visible in a partially overgrown blaze. A 7" Fir bears N 60½°W., 25.1 feet marked X B.T. a location poster bears N 76½°W 6.6 feet
- 3. Painted monument and accessories with bright red paint.



Found BLM brass capped monument marked as shown.

FOUND BLM BRASS CAPPED MOYUMENT MARKED AS SHOWN ATOVE. SKETCH OF CORNER	Jack H. Ninneman t. Signature Organd Party Chief Jack H. Ninneman Signature Organd Party Chief Jack H. Ninneman certify that this Corner Record correctly represents work performed by me or under by direction in ecripitation with the "Corner Recordation Act" (70-22-10), at seq., M.D.A. Signature of Sorw yor & Seat 9/4/81 4661S Date: Ninneman Engineering Inc.
Office of Clerk and Recorder, County of Lincoln ec and was filed for record on the Necember 7th was noted on the cross-index plat and is assigned page No. 1411 book No. 1 Cross Index No. C-31 T	Betty L. Conces ial Deputy