2. Pescription of evident and, note that repancies in the record, state method of extablishing Jost of uniformed corners.

3. Description of monumest and accessories set to perpetuate the corner position.


4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography fles, position of accessories, etc.

Certification must be signed and scaled by Registered Land Surveyor in State of Montana.
 Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner West & Corner Section 2 T. 25N R. 29W P.M.M. Lincoln County

- 1. 40.40 chains: Set a Limestone, 14 X 12 X 12 inches, 9 inches in the ground, for \( \frac{1}{4} \) Section Corner, marked \( \frac{1}{4} \) on the W. face, from which a Tamarack, 14 inches in diameter, bears N 24 E, 64 links distance, marked \( \frac{1}{4} \) S2 B.T. A Tamarack, 10 inches in diameter, bears N81 W 24 links distance, marked \( \frac{1}{4} \) S3 B.T.
- 2. Found: BLM brass capped monument (marked as shown below) from which a 20" Larch bears N24°E 40.3 feet (42.2 record) scribed B.T. visible on partially overgrown blaze. A 14" Larch bears N79°W 15.8 feet (N81°W record) some scribe visible on partially overgrown blaze. A location poster bears S33½°E 14.5 feet. Both bearing trees are original and posted.
- 3. Painted monument and accessories with bright red paint.



Found BLM brass capped monument marked as shown.

