


INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.


CERTIFIED CORNER RECORDATION

Corner C¹ Corner Sec. 2 T. 25N R. 29W P.M.M. Lincoln County

1. This corner not previously set.
2. Set: A 5/8" X 24" rebar (capped with a plastic cap bearing registration No.) from which,
 - A 12" Fir bears N 54°E 25.0 feet scribed C¹S2B.T. and posted.
 - A 16" Fir bears S 10°E 6.3 feet scribed C¹S2B.T. and posted.
 - A location poster on a 3" Fir bears N 20°E 14.5 feet.
 Painted accessories with bright red paint.



5/8" x 24" rebar w/plastic cap stamped as shown.



CERTIFICATION

I, David Stanley
 certify the information shown herein is true and correct.

 Signature Ground Party Chief

I, Jack H. Ninneman
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)

Jack H. Ninneman
 Signature of Surveyor & Seal

Date: Aug. '82 Reg. No. 4661S
 Employer: Ninneman Engineering Inc.

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the Sept. 10 day of 1982 was noted on the cross-index plat and is assigned page No. 1897, in book No. _____

Eleanor L. Vaughn by Betsy L. Conces
 County Official deputy

