## INSTRUCTIONS

- 1. Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- 3. Description of monument and accessories set to perpetuate the corner position.
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

25 N., N 1/4 of Sec. 4 only Lincoln \_\_ P.M.M. . Corner

1903 G.L.O. record by C. H. Albee & W. K. Trippet: "Set a limestone, 14x10x5 ins., 10 ins. in the ground, for 1/4 sec. cor., marked 1/4 on the north face, from which:

A pine, 6 ins. diam., bears N  $21^{\circ}30'$  E, 40 lks. dist., marked 1/4 S 33 BT.

A pine, 8 ins. diam., bears S 59 40' W, 24 lks. dist., marked 1/4 S 4 BT."

1916 Retracement and Resurvey by S. F. Walters, C. Dyson and D. MacRae: The old 1/4 sec. cor. now refers to Sec. 33 only. I therefore obliterate the bearing tree on the south. N 89 50'W continuing measurement, set a shale stone 16x12x4 ins., 10 ins. in the ground for 1/4 sec. cor. of sec. 4 only marked 1/4 on the S. face, from which:


A tamarack, 40 ins. diam., bears S 46  $1/2^{\circ}$ E, 205 lks. dist., mkd. 1/4 S 4 BT. A pine, 6 ins. diam., bears S  $9^{\circ}$ W, 122 lks. dist., mkd. 1/4 S 4 BT.

II. Found a stone, 15x10, 3 ins. above the ground, mkd. 1/4 on the S. face, from which:

A larch stump, 40 ins. diam., bears S 46  $1/2^{\circ}$ E, 135.3 ft., 1/4 S 4 BT visible on long butt alongside on the ground.

A dead pine, 6 ins. diam., bears, S 9 W, 80.5 ft. dist., with visible scribing.

III. At the position of the found stone, set a  $2 \frac{1}{2}$  in. diam. X 30 ins. long aluminum pipe, 24 ins. in the ground, with a 3 1/4 in. diam. aluminum cap mkd. as shown below. Buried the original stone alongside the aluminum pipe.



from which the new bearing trees:

A spruce, 5 ins. diam., bears S  $20^{\circ}$ E, 32.9 ft. dist. mkd. 1/4 S 4 BT. A larch, 12 ins. diam., bears S  $44^{\circ}$ W, 37.5 ft. dist., mkd. 1/4 S 4 BT.

Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs.

20° East Magnetic Declination:

	·
12" LARCH TO DEAD PINE TO STUMP  SKETCH OF CORNER PI 40" STUMP	CERTIFICATION  Kenneth R. Kern  certify the Information shown herein is true and correct.  WWW.  Signature Ground Party Chief  Alvah F. Hughes  certify that this Corner Record correctly represents work performed by me or under my direction in compilance with the Corner Recordation Act. (70-22-101, et seq., M.C.A.)  Signature of Surveyork Seat  12/10/92  Date:  Reg. No.  Employer:  U.S. FOREST SERVICE
Office of Clerk and Recorder, County of	This "corner Sec. MANU
was noted on the cross-index plat and is assigned page No	134 , in

A - 11

Cross Index No. -

County Official

25 N

PMM

· - corner this sheet