1. Original and/or subsequent record used to evaluate the corner position.

2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.

3. Description of monument and accessories set to perpetuate the corner position.

- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner No. 3 Fides MS 6187 T. 25 N. R. 30 W. P.M.M. LINCOLN County

RECORD:

MS NO. 6187 Fides, Robert C. Williams, U.S. Deputy Mineral Surveyor, 1901

1500 S.E. location corner, set a post, 4 ½ ins. square, 5 ft. long, 2 ft. deep, marked 3-6187, for Cor. No. 3, and raised a mound of stone and earth around post.

FOUND:

Found no remaining evidence of the original post, mound of stone or the bearing tree.

TO PERPETUATE:

At record position, set a 5/8" x 24" rebar, with a USFS 3-1/4" aluminum cap 22" in the ground, marked as shown below.

From which new trees:

A lodgepole pine, 9" in diam., bears N.45°E., 18.6', blazed and scribed "3 MS 6187 BT". A lodgepole pine, 7" in diam., bears S.83°W., 12.2', blazed and scribed "3 MS 6187 BT".

Place a "Land Survey Monument" (54-9), and a "Bearing Tree" (54-3) sign on the bearing trees. Painted all blazes red, and a 6" red band above the "Bearing Tree" signs. Placed 6' steel posts on property line, 2'+/- from the corner with "Land Survey Marker" (54-9), and "Property Boundary" (54-2) decals.

See Certificate of Survey, recorded in Lincoln County CERTIFICATION Matt Jacobson certify the information shown herein is true and 342 correct. 839 Signature Ground Party Chief 1.45°E I, R.A. Ainsworth certify that this Corner Record correctly 18.6 FEET represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq. M.C.A.) g"LORGERLE PINE 2000 ignature of Surveyor & Seal H LODGEPAE 11/00 Reg. No. SKETCH OF CORNER Professional Consultants Employer: **Sec.17 This "corner Office of Clerk and Recorder, County of record" was filed for record on was noted on the cross-index plat and is assigned page No. County Official