INSTRUCTIONS

Q:CO-STD/152 Created 4/8/92

- 1. Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
- 3. Description of monument and accessories set to perpetuate the corner position.
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner No. 3 Felicitas MS 6186 T. 25 N. R. 30 W. P.M.M. LINCOLN County

RECORD:

MS NO. 6186 Felicitas, Robert C. Williams, U.S. Deputy Mineral Surveyor, 1901

1500 S.E. location corner, set a post, 4 ½ ins. square, 5 ft. long, 2 ft. deep, marked 3-6186, for Cor. No. 3, and raised a mound of stone and earth around post.

A blazed fir tree, 10 ins. Diam., marked B.T. 3-6186, bears S.23°E., 10 ft.

FOUND:

Found no remaining evidence of the original post, mound of stone or the bearing tree.

TO PERPETUATE:

At record position, set a 5/8" x 24" rebar, with a USFS 3-1/4" aluminum cap 23" in the ground, marked as shown below.

From which new trees:

A fir, 12" in diam., bears S.31°E., 8.5', blazed and scribed "3 MS 6186 BT". A lodgepole pine, 12" in diam., bears S.29°W., 6.2', blazed and scribed "3 MS 6186 BT".

Place a "Land Survey Monument" (54-9), and a "Bearing Tree" (54-3) sign on the bearing trees. Painted all blazes red, and a 6" red band above the "Bearing Tree" signs. Placed 6' steel posts on property line, 3'+/- from the corner with "Land Survey Marker" (54-9), and "Property Boundary" (54-2) decals.

	CERTIFICATION
SOA FOREST SEALER	I, Matt Jacobson certify the information shown herein is true and correct. Signature Ground Party Chief I. R.A. Ainsworth
CADASTRAL SURVEY 12"LODGE POLE PINE 12" FIR	represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.) Signature of Surveyor & Sealth Date: 11/00 Reg. No. 29238' S
SKETCH OF CORNER	Employer: Professional Consultants, Inc.
Office of Clerk and Recorder, County of Amed. This "corner record" was filed for record on	
30 , 3	

See Certificate of Survey, recorded in Lincoln County