

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing, lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

**• CERTIFIED CORNER RECORDATION**

Corner Maunder Corner between Sec. 10 & 11 - N. Shore Thompson Lake  
 T. 26N R. 27W P.M.M. Lincoln County

Record: Set a limestone 15x10x6 ins. 10ins in the ground marked MC on South face with 2 grooves on E. face.

from which:

- a fir 12" diam. bears N. 33° 30' E. 841ks
- a fir 14" diam. bears N. 49° W. 361ks.

Found original stone MC on South face  
 See C.O.F.S. No. 339 for adjacent corners.

CERTIFICATION

I, \_\_\_\_\_  
 certify the information shown herein is true and correct.

Signature Ground Party Chief

D.K. Mauquardt

I certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)

D.K. Mauquardt  
 Signature of Surveyor & Seal

Date: 7-15-81 Reg. No. 2089ES


Employer: \_\_\_\_\_

SKETCH OF CORNER

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the 12<sup>th</sup> August day of 1981, was noted on the cross-index plat and is assigned page No. 1183, in book No. 1

Deanna L. Vaughn, by Betty Bell,  
 County Official Deputy

Sec. 10



Cross Index No. F-G 17 T. 26N R. 27W P.M.M.

• - corner this sheet