

1/4  
Corner 33 | 34 T. 26 N. R. 28 W. P.M.M. Lincoln County

# CERTIFIED CORNER RECORDATION

1903 G.L.O. Survey by Charles H. Albee and William K. Trippet in Book 4296 Page 54  
"Set a sandstone, 12x10x5 ins., 8 ins. in the ground, for 1/4 sec. cor., marked 1/4 on W. face; from which  
A fir, 8 ins. diam., bears S.34E., 32 lks. dist., marked 1/4 S 34 B T.  
A fir, 10 ins. diam., bears N.86°30'W., 41 lks. dist., marked 1/4 S 33 B T."

Survey by J. E. Owens, filed as Certificate of Survey No. 590, on April 14, 1977, describes corner as "Brass Cap BLM".  
No Corner Recordation filed.

Survey by D. K. Marquardt, filed as Certificate of Survey No. 1055, on November 10, 1982, describes corner as  
"BLM Brass Cap Per C of S No. 590". No Corner Recordation filed.

1999 Remonumentation by S. R. Smith  
I find the original GLO stone (14"x8"x5") marked "1/4" on west face. I also find original bearing trees as described below. I find no evidence of a "BLM Brass Cap", nor do I find any record that the BLM ever remonumented this corner. It appears that neither Owens nor Marquardt ever tied this corner, and it should be noted that the boundaries which they staked which relied on this corner position will be incorrect. (See Certificate of Survey No. 590 - Owens and Certificate of Survey No. 1055 - Marquardt.)

At the position marked by the found stone, I set an aluminum pipe, 2 1/2" diameter, 30" long, with 3 1/4" diameter Montana Department of Highways aluminum cap, marked as shown below. I buried the original stone, upside down, at the base of the aluminum monument. Top of cap is 6" above ground, from which,

I find original bearing trees as follows:

A fir, 16" DBH, with overgrown face blaze, bears South 34° East 21.90' distant.

A fir stump, 16" DBH, bears North 86°30' West, 36.80' distant. I opened the blaze of this stump to expose scribing "4 S 33".

I establish one new bearing tree as follows:


A fir, 8" DBH, blazed and scribed "1/4 S34 BT", bears North 37°30' East, 53.80 feet distant.

A 3 1/2' long galvanized steel post with M.D.T. survey decal attached, bears South, 1.0' distant.

I marked the two live trees with a snow blaze and painted red bands at blaze height. Placed Bearing Tree signs on both trees.

Bearings listed above in remonumentation section were measured with a hand compass, declination 19 1/2° East. Distance was measured to center of tree.

Refer to the Certificate of Survey filed in conjunction with this Corner Recordation for ties to adjacent section controlling corners.




## SKETCH OF CORNER

CERTIFICATION	
I, R. K. Wunderlich,	
certify the information above is true and correct.	
<i>R.K. Wunderlich</i>	Signature Ground Party Chief
I, S. R. Smith,	
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (MCA 22-1-101, et seq., M.C.A.)	
<i>S. R. Smith</i>	Signature of Surveyor Seal
Date: 04/09/99	4740S
Employer: Smith Surveying	

Office of Clerk and Recorder, County of Lincoln . This "corner record" was filed for record on 12/10/2001 was noted on the cross-index plat and is assigned page No. 10547 in book No. Coral M. Cunningham, County Official

Cross Index No. X-13 T. 26 N. R. 28 W. PMM

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors



corner this sheet

f:\clients\mdt-ka\00\pww\corner (10)