CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Record- Set sandstone 12x10x5 in. 8 in. in ground mkd. $\frac{1}{4}$ on North face. Found- No evidence found

Record- Fir 6" dia. bears N27°15'E 18 lks. mkd. $\frac{1}{4}$ S11 BT.

Found- No evidence found

Record- Pine 36 In. dia. bears $506^{\circ}30'W$ 34 lks. mkd. $\frac{1}{4}$ S14 BT. Found- No evidence found.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 11/80

Set aluminum post 27" long, 21" dia. with aluminum cap 20" in ground, from which:

A Fir 7" dia. bears NO4°E 19.5 ft. mkd. $\frac{1}{4}$ S BT. A Fir 8" dia. bears S24°W 16.2 ft. mkd. $\frac{1}{4}$ S BT.

Corner set by single proportion.

Sketch of alum. cap



SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE C.O.S. NO. 899

Surveyor's Seal



certify that the information shown herein is true and correct.

Signature of Ground Party Chief

H. Gene Warren

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

> Time Warren Signature of Surveyor

DIAGRAM OF CORNER:

76 N 28 W

H

= Corner recorded on the sheet

2734-5 Registration Number

Office of Clerk and Recorder, County of.....

This "corner record" was filed for record on the day

assigned page No. 1058 in book No.

County Official Cross Index No. J-19 T ZG N

R. 78 W Mer.