## **CERTIFIED LAND CORNER RECORDATION**

(REFERENCE FSM 7153.53)

## DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Record- Set iron post 30"x21" in ground with brass cap. Piled stone alongside. Buried original stone alongside post.

Found- Iron post w/ brass cap record description.

Record. - Fir 9 in. dia. bears  $N69\frac{1}{2}$  OE 49 lks. mkd.  $\frac{1}{4}$ S13 BT. Found- Fir record dist. and bearing w/ scribing evident.

Record- Pine 28 in. dia. bears  $N88\frac{1}{2}$  W 261ks. mkd.  $\frac{1}{4}$  S14 BT. Found- Pine record dist. and bearing w/ scribing evident.

> DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

> > Date of work: 11/80

As corner was in good shape, along with its accessories, left corner as indicated in record. Repainted bearing trees.

Sketch of brass cap

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE C.O.S. NO. 899

Surveyor's Seal



H. Gene Warren certify that the information shown herein is true and correct.

Signature of Ground Party Chief

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

> une Warm Signature of Surveyor

DIAGRAM OF CORNER: RZBW

= Corner recorded on the sheet

2734-5 Registration Number

Office of Clerk and Recorder, County of..... T-51 T 26N 28 W

Cross Index No.