CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Record- Set iron post 30"x2½" with brass cap 27" in ground, with original stone buried alongside.

Found- Record iron post w/ brass cap.

Record- Fir 17 in. dia. bears NO5°E 29 lks. mkd. ½ S14 BT.

Found- Fir record dist. and bearing w/ scribing evident.

Record- Pine 30 in. dia. bears S34½°E 25lks. mkd. ½ S23 BT.

Found- Pine record dist. and bearing w/ scribing evident.

Record- Larch 6 in. dia. bears S11°E 31lks. mkd. ½ S23 BT.

Found- Larch record dist. and hearing w/ scribing evident.

Found- Larch record dist. and bearing w/ scribing evident.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 11/80

As corner and accessories were in good condition, left corner as described in record. Repainted bearing trees.



Sketch of brass cap

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

See C.O. S. No. 899

MAN ON TA H. GENE WARREN 2734 S PEGISTERED SURVE

Surveyor's Seal

H. Gene Warren certify that the information shown herein is true and correct.

Signature of Ground Party Chief

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Signature of Surveyor

DIAGRAM OF CORNER:

26 N PMM R 28W

= Corner recorded on the sheet

2734-5

Registration Number

Office of Clerk and Recorder, County of This "corner record" was filed for record on the day of 198...., was noted on the cross-index plat and is County Official 19mm Cross Index No. N-19 T. 26 N R ZSW .. Mer.