CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Record- Set iron post $30"x2\frac{1}{2}"$ with brass cap 27" in ground. Buried remains of original wood post alongside. Found- Record iron post w/ brass cap set firmly in gorund. Record- Pine 10 in. dia. bears \$56\frac{1}{4}^{OE}\$ 13lks. mkd. \frac{1}{4}\$ \$10 BT. Found- Pine record dist. and bearing w/ scribing evident. Record- Larch 7 in. dia. bears \$N42^{OW}\$ 12lks. mkd. \frac{1}{4}\$ \$9 BT. Found- Larch record dist and bearing w/ scribing evident.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 11/80

As corner and accessories were in good condition, left corner as Repainted bering trees. described in record.

የշራN RZBiu

Sketch of brass cap

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

SEE C.O.S. NO. ****

I, H. Gene Warren

H. GENE WARREN 2734 S SURVE	certify that the information shown herein is true and correct.
	Signature of Ground Party Chief
	I, certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. Signature of Surveyor

Surveyor's Seal

DIAGRAM OF CORNER: TZGN RZ8W = Corner recorded on the sheet

2734-5 Registration Number

Office of Clerk and Recorder, County of This "corner record" was filed for record on the day of 19. was noted on the cross-index plat County Official assigned page No. 1080 , in book No. Cross Index No. G-13 T Z6 N R 28 W

, t Triples of the state of the state of .