

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

At the corner common to secs. 32, 33, 5, and 4, T.'s 25 and 26 N., R. 28 W., I found the original corner stone, 14 x 10 x 6 inches, firmly set 10 inches into the ground, 4 notches on east face and 2 notches on west face.
(Record: Same.)

From which:

A 21-inch Douglas-fir snag bears N. 80° E., 19 links, scribing overgrown.
(Record: 20-inch fir bears N. $79^{\circ}30'$ E., 17 links.)

A 20-inch Douglas-fir snag bears S. 52° E., 28 links, scribing overgrown.
(Record: A 20-inch fir bears S. 52° E., 27 links.)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

A 13-inch Douglas-fir snag bears S. 38° W., 28 links, scribing overgrown.
(Record: 10-inch fir bears S. $38^{\circ}45'$ W., 28 links.)

Date of work: May 18, 1964

An 11-inch Douglas-fir bears N. 80° W., 9 links, scribing "T. 26 N., R. 28 W., sec. 32" visible; tree alive and in good condition.
(Record: 10-inch fir bears N. 80° W., 20 links.) Actual in the field.

I set a 2-inch galvanized iron pipe 26 inches into ground at center point of original stone with brass cap on pipe marked:

T. 26 N., R. 28 W.,

S 32	S 33
S 5	S 4

T. 25 N.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.) 858ES -- IMT -- ART

I buried the original stone alongside the iron pipe,

From which:

9-inch white fir bears N. 39° E. 44 links, scribed "S 33 RM."
5-inch spruce bears S. $70\frac{1}{2}^{\circ}$ E., 26 links, scribed "S 4 RM."
8-inch white fir bears S. 47° W., 40 links, scribed "S 5 RM."

(Record from original GLO notes)

Surveyor's Seal

I, A. R. Trenkle
certify that the information shown herein is true and correct.

A. R. Trenkle

Signature of Ground Party Chief

I, Ira M. Tillotson
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Ira M. Tillotson

Signature of Surveyor

DIAGRAM OF CORNER:

N.
↑

T. 26 N., R. 28 W.

S 32	S 33
S 5	S 4

T. 25 N., R. 28 W.

◇ = Corner recorded on the sheet

858ES

Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 4th day of SEPTEMBER 1964, was noted on the cross-index plat and is

assigned page No. 11, in book No. 1

M. M. MANSFIELD, By: Ira M. Tillotson Deputy.
County Official

Cross Index No. Z 9 T. 26 N. R. 28 W. P.M.M.
A 9 25 28 Mer.