## INSTRUCTIONS

- 1. Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
- 3. Description of monument and accessories set to perpetuate the corner position.
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

## **CERTIFIED CORNER RECORDATION**

Corner: C-W-NE 1/64th; Sec. 28

T. 26N.

R. 28W. P.M.M. Lincoln County

Record:

No previous record

Found:

No evidence found

2009 Perpetuation:

At a position established by the survey and section breakdown of Section 28, we set a 5/8"x30" rebar, 24" in the ground affixed with a 3 1/4" U.S.F.S. alum cap, marked as shown below, from which we establish the following reference monuments:


> A 9" Douglas fir, bears \$16°E, 28.0 ft., with an "X" cut at breast height A 13" Douglas fir, bears N89°E, 11.2 ft., scribed CWNE 1/64 S28 BT

We build a mound of stone around the monument.

We set galvanized steel posts with USFS decals P54-1 & P71-10, north, 1.4 ft. and west, 1.0 ft. of the monument.

We paint red bands on the bearing trees and attach USFS signs 54-3 & 54-9.

SEE COS NO. 3991



	Sec. 28		
Office of Clerk and Recorder, County of This "corner	<u> </u>	Т	
record" was filed for record on 224826 BOOK: CCR CCGR'S PAGE: 11452 Pages: 1			•
was noted on the cross-ing state of montana lincoln county  RECORDED: 03/05/2010 8:55 KOI: CCER'S		$\Box$	
book No TAMMY D. LAUER CLERK AND RECORDER  FEE: \$0.00 By Beanne Learne depute			
TO: MONTANA MORTHWEST COMPANY P.O. BOX 8777, MISSOULA, MONTANA			

Cross Index No.

S-11.5 T. 26N R 28W PMM

Corner this sheet