

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

CERTIFIED CORNER RECORDATION

Corner: 1/4 Corner; Secs. 27 & 28 T. 26N. R. 28W. P.M.M. Lincoln County

GLO
1903 Record: Set 16"x10"x4" stone. Established 2 BTs

1964 BLM Record: Found orig. stone & 2 BTs.
Set an iron post, 30 ins. long, 2 1/2" ins. diam., 27 ins. in the ground with brass cap, from which:
A 15" fir, bears S79°E, 35 lks (23.1 ft.), with visible marks 1/4 S27
A 15" fir, bears N41°W, 14 lks (9.2 ft.), with visible marks 1/4 S28

2009 Found: We find a standard BLM monument with a 3 1/4" BLM brass cap, firmly set in good condition, rising 6" above the ground, marked as shown below, from which:
A 20" Douglas fir, bears N41°W, 9.2 ft., with scribing visible
An 18" fir stump, 2.5' high, bears S79°E, 23.1 ft., bottom of blaze visible

2009 Perpetuation: From the found monument we establish the following reference monument:
A 10" Douglas fir, bears S58°W, 8.5 ft., scribed 1/4 S28 BT

We set a galvanized steel post with USFS decals P54-1 & P71-10, 1.0 ft. north of monument.
We paint red bands on the existing bearing tree, and attached USFS signs 54-3 & 54-9.
We create a larger mound of stone around the monument.

SEE COS NO. 3991

SKETCH OF CORNER

CERTIFICATION

I, Chad R. Breuer
certify the information shown herein is true and correct.
Chad R. Breuer
Signature Ground Party Chief

I, Ken E. Jenkins
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the Montana Recordation Act" (70-22-101, et seq.).
Ken E. Jenkins
Signature of Surveyor & Seal

Date: 8/2009 Reg. No. 9330 LS
Employer: Montana Northwest Company
PO Box 8777, Missoula, MT 59807
406-721-4033 Project No. 1617-09

Office of Clerk and Recorder, County of _____ This "corner record" was filed for record 224828 BOOK: CCR CC&R'S PAGE: 11454 Pages: 1 was noted on the cross-index STATE OF MONTANA LINCOLN COUNTY RECORDED: 03/05/2010 8:57 KOI: CC&R'S TAMMY D. LAUER CLERK AND RECORDER FEE: \$0.00 BY: *Tammy D. Lauer* TO: MONTANA NORTHWEST COMPANY P.O. BOX 8777, MISSOULA, MONTANA

Sec. 28

Cross Index No. T-13 T. 26N R. 28W PMM

● Corner this sheet