## CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

At the corner common to secs. 30, 29, 31, and 32, T. 26 N., R. 28 W., I found the original corner stone,  $12 \times 10 \times 5$  inches, loosely set with 1 notch on south face and 5 notches on east face. (Record: Same.)

From which:

An 8-inch larch bears N. 11° E., 45 links, scribing partly overgrown; "R 2" visible. (Record: 6-inch pine bears N. 11° E., 45 links.)

A 7-inch lodgepole pine bears S. 85°45' E., 49 links, scribing R 28 W., sec. 32" visible. (Record: 5-inch pine, S. 85°45' E., 69 links.) Actual in the field.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED

TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: A 16-inch larch snag bears S. 13 W., 9 links, scribing

Date of work: May 19, 1964

"T. 26 N., R. 28 W., sec. 31" visible. (Record: 18-inch pine, S. 19030' W., 9 links.) Actual in the field. T. 26 N., R. 28 W.

A 9-inch lodgepole pine bears N. 42°30' W., 37 links, scribing "T. 26 N., R. 28 W., sec. 30 BT" visible. (Record: 6-inch pine bears N. 42030' W., 37 links.)

1964

I set a 2-inch galvanized iron pipe 26 inches into ground at center point of original stone with brass cap marked:

858ES -- IMT -- ART

I buried the original stone alongside the iron pipe, from which 10-inch lodgepole pine bears S. 24° W., 51 links, scribed "S. 31 RM."

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.

(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original GLO notes.)

Surveyor's Seal

I, A. R. Trenkle certify that the information shown herein is true and correct.

> a.B. Trenkle Signature of Ground Party Chief

T. 26 N., R. 28 W.

DIAGRAM OF CORNER:

Ira M. Tillotson

certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same

0

Signature of Surveyor

= Corner recorded on the sheet

858ES Registration Number

Office of Clerk and Recorder, County of Lincoln This "corner record" was filed for record on the 4th. day of SEPTEMBER 19.64, was noted on the cross-index plat and is M. M. MANSFIELD, By: // County Official Watern, Deputy By: ///ae assigned page No. 12 in book No. 1 Cross Index No. V 5 T. 26 N., R.