CERTIFIED LAND CORNER RECORDATION
(Reference FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

At the 1/4 corner common to secs. 5 and 32, T.'s 25 and 26 N., R. 28 W., I found the original stone, 12 x 10 x 5 inches, firmly set 8 inches into the ground with "1/4" on north face.
(Record: Same.)

From which:

An 8-inch lodgepole pine bears S. 27°45' W., 19 links, scribed "1/4 S 5 BT."
The tree is alive and in good condition.
(Record: 7-inch pine bears S. 27°45' W., 19 links.)

A 10-inch lodgepole pine bears N. 36°10' W., 19 links, scribed "1/4 S 32 BT."
The tree is alive and in good condition.
(Record: 8-inch pine bears N. 36°10' W., 19 links.)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

I set a 2-inch galvanized iron pipe 26 inches into the ground at center point of the original stone with brass cap marked:

I buried the original stone alongside the iron pipe, from which

(Record: Same)

Date of work: May 19, 1964

T. 26 N., R. 28 W.,

$\frac{1/4 \ S \ 32}{S \ 5}$

T. 25 N.,

858ES -- IMT -- ART

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original GLO notes.)

Surveyor's Seal

I, ...A. R. Trenkle......
certify that the information shown herein is true and correct.

G. R. Trenkle
Signature of Ground Party Chief

I, ...Ira M. Tillotson......
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Ira M. Tillotson
Signature of Surveyor

858ES
Registration Number

DIAGRAM OF CORNER:

N.

↑   T. 26 N., R. 28 W.

$\frac{1}{4}$ $\frac{S \ 32}{S \ 5}$

T. 25 N., R. 28 W.

◊ = Corner recorded on the sheet