CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN) At the 1/4 corner common to secs. 33 and 4, T.'s 25 and 26 N., R. 28 W., I found original corner stone, $18 \times 10 \times 8$ inches, firmly set 14 inches into ground with "1/4" on north face. (Record: Same.) From which: A 16-inch spruce stump bears N. 64° E., 9 links, scribed "1/4 S 33." Record: 12-inch spruce bears N. 62°10' E., 8 links.) A 16-inch spruce stump bears S. 10° E., 19 links, scribing rotted beyond recognition. (Record: 8-inch spruce, S. 10°39' E., 19 links.) DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER: Date of work: May 18, 1964 I set a 2-inch galvanized iron pipe 26 inches into ground at the center point of original stone with brass cap marked: T. 26 N., R. 28 W. 1/4 <u>s 33</u> I buried the original stone alongside the iron pipe, From which: 11-inch larch bears N. $44\frac{10}{2}$ W., 25 links, scribed "S 33 RM." 12-inch spruce bears S. $62\frac{10}{2}$ W., 32 links, scribed "S 4 RM." T. 25 N. 1964 858 ES - IMT - ART SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.) (Record from original GLO notes.) DIAGRAM OF CORNER: A. R. Trenkle Surveyor's Seal certify that the information shown herein is true and T. 26 N., R. 28 W. correct. a.R. Treullo Signature of Ground Party Chief T. 25 N., R. 28 W Ira M. Tillotson certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same. Corner recorded on the sheet of Surveyor 858ES Registration Number Office of Clerk and Recorder, County of Lincoln

assigned page No. 15, in book No. 1

This "corner record" was filed for record on the 4th. day of SEPTEMBER 19.64, was noted on the cross-index plat and is M. M. MANSFIELD, By: M. County Official Malan Deputy P.M.M. Cross Index No. Z 11 T. 28