

CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

FOUND 10" X 12" STONE WITH 1/4 ON WEST FACE

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 9/25/78

8" fir scribed 1/4 RM

FOUND STONE

8" pine scribed 1/4 RM

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

FOUND STONE

SEC. B
N00°09'10"E

2641.10'

BRASS CAP

Surveyor's Seal

I, THOMAS E. SANDS
certify that the information shown herein is true and correct.


Thomas E. Sands
Signature of Ground Party Chief

C.W. DOYLE

I, _____
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

C. W. Doyle
Signature of Surveyor

DIAGRAM OF CORNER:



⊙ = Corner recorded on the sheet

2516-S

Registration Number

Office of Clerk and Recorder, County of Lincoln
This "corner record" was filed for record on the 12th day of October, 1978, was noted on the cross-index plat and is assigned page No. 537, in book No. _____
Thomas E. Sands by Betty Paul
County Official Deputy
Cross Index No. _____ T. 26N R. 28W Mer.