INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.

- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
- 3. Description of monument and accessories set to perpetuate the corner position.
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

CERTIFIED CORNER RECORDATION

Corner: N 1/16th; Secs. 13 & 14

T. <u>26N.</u>

R. 29W. P.M.M. Lincoln County

Record: Found:

No previous record No evidence found

2009 Perpetuation:

At a position established by the survey and section breakdown of Section 14, we set a 5/8" rebar,

with a 3-1/4" U.S.F.S. alum cap, 0.3 ft. above the ground, marked as shown below, from which

we establish the following reference monuments:

A 7" Douglas fir, bears S55°E, 3.7 ft., scribed N 1/16 S13 BT An 8" Douglas fir, bears S13°W, 4.8 ft., scribed N 1/16 S14 BT


Position of the corner is in a large dugout terrace of a road embankment.

We build a mound of stone around the monument.

We set a galvanized steel posts with U.S.F.S. decals P54-1 & P71-10, 4.0 ft., south and 1.8 ft., west of the monument.

We paint red bands on the bearing trees and attach U.S.F.S. signs 54-3 & 54-9.

SEE COS NO. 3990



	•	Sec. 14		
Office of Clerk and Recorder, Co	unty of This "corner			
record" was filed for record on _	224841 BOOK: CCR CC&R'S PAGE: 11467 Pages: 1			
	STATE OF MONTANA LINCOLN COUNTY			
book No	RECORDED: 03/05/2010 9:10 KOI: CCGR'S TAMMY D. LAUER CLERK AND RECORDER			
	TO: MONTANA HORTHWEST COMPANY P.O. BOX 8777, MISSOULA, MONTANA		<u> </u>	iJ

Cross Index No.

K-21 T. 26N R 29W PMM

Corner this sheet