## INSTRUCTIONS

- 1. Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
- 3. Description of monument and accessories set to perpetuate the corner position.
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of
- 5. Certification must be signed and scaled by Land Surveyor registered in the State of Montana.

## CERTIFIED CORNER RECORDATION

Corner: CS 1/16th; Sec. 14

R. 29W. P.M.M. Lincoln County

Record:

No previous record

Found:

No evidence found

2009 Perpetuation:

At a position established by the survey and section breakdown of Section 14, we set a 5/8"rebar, with a 3 1/4" U.S.F.S. alum cap, 0.4 ft. above the ground, marked as shown below, from which, we establish the following reference monuments:


An 8" larch, bears N61°E, 18.5 ft., scribed CS 1/16 S14 BT A 15" Ponderosa pine, bears N35°W, 20.7 ft., scribed CS 1/16 S14 BT

We build a mound of stone around the monument.

We set galvanized steel posts with U.S.F.S. decals P54-1 & P71-10, 2.3 ft., north and 3.0 ft., east of the monument.3

We paint red bands on the bearing trees and attach U.S.F.S. signs 54-3 & 54-9.

SEE COS NO. 3990



		Sec. 14		
Office of Clerk and Recorder, Coun	ty of This "corner	П		
record" was filed for record on	224845 BOOK: CCR CCER'S PAGE: 11471 Pages: 1	$\vdash$		
was noted on the cross-index plat a			_	-
book No.	TAMMY D. LAUER CLERK AND RECORDER		-	
	TO: MONTANA NORTHWEST COMPANY P.O. BOX 8777, MISSOULA, MONTANA	<u> </u>	L	

Cross Index No.

M-19 T. 26N R 29W PMM

Corner this sheet