

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

### CERTIFIED CORNER RECORDATION

Corner: 1/4 Corner; Secs. 14 & 23 T. 26N. R. 29W. P.M.M. Lincoln County

1903 GLO Record: Set stone & established 2 bearing trees

1964 BLM Record: Found orig. stone and remains of 1 bearing tree  
 Set iron post, 30 ins. long, 2 1/2 ins. dia., 27" in the ground, with a 3 1/4" brass cap.  
 Original bearing tree:  
 A 36" stump, bears N11-3/4°W, 5 lks (3.3 ft.), marked 1/4S14BT  
 New bearing trees:  
 A 6" pine, bears S58°W, 23 lks (15.2 ft.), marked 1/4 S23 BT  
 A 7" pine, bears N60°W, 23 lks (15.2 ft.), marked 1/4 S14 BT  
 Buried orig. stone alongside

2009 Found: We find a standard BLM monument with a 3 1/4" brass cap, firmly set, in good condition, rising 6" above the ground, marked as shown below, from which:  
 A 38" stump, bears N11 3/4°W, 3.3 ft., with partially visible scribing  
 A 13" Ponderosa pine, bears N60°W, 15.2 ft., with overgrown blaze & BT tag

2009 Perpetuation: From the found monument we establish the following reference monument:  
 An 8" larch, bears N40°E, 13.7 ft., scribed 1/4 S14 BT

We paint red bands on the existing bearing trees, and attached USFS signs 54-3 & 54-9.  
 We create a larger mound of stone around the monument.

SEE COS NO. 3990

**SKETCH OF CORNER**

**CERTIFICATION**

I, Chad R. Breuer  
 certify the information shown herein is true and correct.  
*Chad R. Breuer*  
 Signature Ground Party Chief

I, Ken E Jenkins  
 certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101) et seq., M.T.A.  
*Ken E Jenkins*  
 Signature of Surveyor & Seal  
 JENKINS I. 933013  
 REGISTERED SURVEYOR

Date: 9/2009 Reg. No. 933013  
 Employer: Montana Northwest Company  
PO Box 8777, Missoula, MT 59807  
406-721-4033 Project No. 1617-09

Office of Clerk and Recorder, County of \_\_\_\_\_ This "corner record" was filed for record on \_\_\_\_\_ **224848 BOOK: CCR CC&R'S PAGE: 11474 Pages: 1**  
 was noted on the cross-index plat and **STATE OF MONTANA LINCOLN COUNTY**  
 book No. \_\_\_\_\_ **RECORDED: 03/05/2010 9:16 KOI: CC&R'S**  
**TAMMY D. LAUER CLERK AND RECORDER**  
**FEE: \$0.00 BY: *Seannie Lauer***  
**TO: MONTANA NORTHWEST COMPANY P.O. BOX 8777, MISSOULA, MONTANA**

Sec. 14


Cross Index No. N-19 T. 26N R. 29W PMM ● Corner this sheet