## INSTRUCTIONS



- 1. Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.

3. Description of monument and accessories set to perpetuate the corner position.

- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

## CERTIFIED CORNER RECORDATION

Corner: S-N 1/64th; Sec. 33, 34

T. 26N.

R. 29W. P.M.M. Lincoln County

Record:

No previous record

Found:

No evidence found

2009 Perpetuation:

At a position established by the survey and section breakdown of Section 34, we set a 5/8"x30" rebar, 24" in the ground affixed with a 3 1/4" U.S.F.S. alum cap, marked as shown below, from which we establish the following reference monuments:


A 7" Lodgepole pine, bears South, 1.8 ft., with an "X" cut at breast height An 8" Lodgepole pine, bears S73°E, 11.0 ft., scribed SN 1/64 S34 BT with an existing quarter blaze

We build a mound of stone around the monument.

We set galvanized steel posts with USFS decals P54-1 & P71-10, south, 0.9 ft. and east, 0.7 ft. of the monument.

We paint red bands on the bearing trees and attach USFS signs 54-3 & 54-9.

SEE COS NO. 3992



		Sec. 34			
Office of Clerk and Recorder, Count	y of This "corner			$\Box$	1
record" was filed for record on	224865 BOOK: CCR CCGR'S PAGE: 11492 Pages: 1		<del>                                     </del>	+	ł
was noted on the cross-index plat ar	224866 BOOK: CCR CCER'S PAGE: 11492 Pages: 1 ( STATE OF MONTANA LINCOLN COUNTY			_	1
book No.	RECORDED: 03/05/2010 9:34 KOI: CCER'S TAMMY D. LAUER CLERK AND RECORDER	-		-}-	1
	FEE: 80.00 BY: See Sellow Back	<u></u>			J

Cross Index No.

<u>W.5-13</u> T. <u>26N</u> R <u>29W</u> PMM

Corner this sheet