

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories,
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

CERTIFIED CORNER RECORDATION

Corner: 1/4 Corner, Secs. 34&35 T. 26N. R. 29W. P.M.M. Lincoln County

GLO 1903 Record: Set limestone, 14x10x5 ins., 11 ins. in the ground, marked 1/4 on W. Face; from which:
 A fir, 10 ins. diam., bears N49°30'E, 41 lks. (27.1 feet)
 A fir, 12 ins. diam., bears N53°30'W, 18 lks. (11.9 feet)

2009 Found: We find a broken limestone, 14"x10"x6", with 1/4 visible on face, lying on ground, 2 ft. southeast of a distance-distance intersection from the remains of the original bearing trees.

2009 Perpetuation: We set a 5/8"x30" rebar, 24" in the ground affixed with a 3 1/4" U.S.F.S. aluminum cap at the position determined by a distance-distance intersection from the remains of the original bearing trees, from which:

Original bearing trees

- A rotten stump, flush with ground bears N49°30'E, 27.1 feet (GLO Record)
- A rotten stump, flush with ground bears N53°30'W, 11.9 feet (GLO Record)

New reference monuments

- A 24" Ponderosa pine, bears N82°W, 35.1 ft., scribed 1/4 S34 BT
- A 17" Douglas fir, bears N27°W, 21.3 ft., scribed 1/4 S34 BT


We build a mound of stone around the monument.

We bury the stone face down along the south side of monument.

We establish the following reference monuments:


We set a galvanized steel post with USFS decals P54-1 & P71-10, south, 1.4 ft. of the monument. We paint red bands on the bearing trees and attach USFS signs 54-3 & 54-9.

SEE COS NO. 3992

| | |
|--|---|
|  <p>SKETCH OF CORNER</p> | <p style="text-align: center;">CERTIFICATION</p> <p>I, <u>Chad R. Breuer</u> certify the information shown herein is true and correct. <i>Chad R. Breuer</i> Signature Ground Party Chief</p> <p>I, <u>Ken E Jenkins</u> certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the Corner Recordation Act" (70-22-101, et seq.; M.C.A.) <i>Ken E Jenkins</i> Signature of Surveyor</p> <p>Date: <u>9/2009</u> Reg. No. <u>9330LS</u> Employer: <u>Montana Northwest Company</u> <u>PO Box 8777, Missoula, MT 59807</u> <u>406-721-4033 Project No. 1617-09</u></p> |
|--|---|

Office of Clerk and Recorder, County of _____ This "corner record" was filed for record on _____
 was noted on the cross-index plate _____
 book No. _____

224869 BOOK: CCR CC&R'S PAGE: 11495 Pages: 1
 STATE OF MONTANA LINCOLN COUNTY
 RECORDED: 03/05/2010 9:37 KOI: CC&R'S
 TAMMY D. LAUER CLERK AND RECORDER
 FEE: \$0.00 BY: *Tammy D. Lauer*
 (TO: MONTANA NORTHWEST COMPANY P.O. BOX 8777, MISSOULA, MONTANA



Cross Index No. X-17 T. 26N R 29W PMM

● Corner this sheet