## INSTRUCTIONS

- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

3. Description of monument and accessories set to perpetuate the corner position.

- Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- topography ites, position of accessories, etc.

  5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.

  6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner	East & Corner Sec	36 . 7	r. <u>26</u> N	R. <u>29</u> W	P.M.M.	Lincoln	County
--------	-------------------	--------	----------------	----------------	--------	---------	--------

- 1. 40 chains: Set a sandstone 24 X 10 X 8 ins., 18 ins. in the ground for \$ Seg corner marked 4 on West face; from which a Tamarack 6ins. diam., bears S 72 35 lks. distance, marked  $\frac{1}{4}$  S 31 B.T. A Pine 8 ins. diameter, bears S  $69^{\circ}$ W 9 lks. distance, marked 4 S 36 B.T.
- 2. Found: original stone scribed  $\frac{1}{4}$  on west face from which a 10" Larch bears S  $68^{\circ}$ E 23.0 ft. The upper blaze has been opened by others, the scribed number 4 is plainly visible. Tree was posted by S.D.S. 11/79. A 12" Pine bears N  $60^{\rm O}$  W 12.0 ft. blazed as bearing tree overgrown I do not open blaze. Posted by S.D.S. 11/79.
- 3. I replace stone with a 3" aluminum monument on a 30" pipe and bury original stone along side. No rocks available within 150 ft. paint monument red. An 8" Larch bears N 30°E 19.0 ft. scribed 1 S 31 B.T. posted and painted. An 8" Pine bears S 64° W 23.1 ft. scribed 1 S 36 B.T. posted and painted. A 10" Larch with location poster bears S 43°E 15.6 ft. attention poster (54-4) is attached to a 10" Larch, bearing and distance not recorded.



536   531   m   set 3 armirrium monument ma	arked as shown.
FND. 12"BNE PAGE  FND. 0RIG STONE SCRIBED  YA ON WEST FACE  REPLACED WITH MON.  AS SHOWN ABOVE  10" LARCH  SKETCH OF CORNER ON 10" LARCH  SKETCH OF CORNER ON 10" LARCH	CERTIFICATION  I. Jack H. Ninneman certify the information shown herein is true and correct.  Signature Ground Party Chief  I. Jack H. Ninneman certify that this Corner Record correctly represents work performed by me or under by direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)  Signature of Surveyor & Seal  Date: 9/23/8 keg. No. 46615  Employer:  Employer:
office of Clerk and Recorder, County of Lineals record" was filed for record on the Market 5th was noted on the cross-index plat and is assigned page No. 139 book No	by Botty & Concer -

26N

- corner this sheet