- 1. Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated

- Description of monument and accessories set to perpetuate the corner position.
 Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

 5. Certification must be signed and scaled by Registered Land Surveyor in State of Montana.

 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

East & Corner Section 25 T. 26N R. <u>30</u>W P.M.M. Lincoln _County |

- 1. 40 chains: Set an iron post 3 feet long 1 inch in diameter, 24" in the ground, for 1/4 Section Corner for Section 25 only, with Brass cap marked 1/4\$25/1916 and raise a mound of stone 2 ft. base 12 ft. high W. of corner.
- 2. Found: 1916 brass cap from which a 10" Pine bears N $85^{\circ}W$ 7 links scribed, but grown over. An 8" Pine bears S $11^{\circ}E$ 11 links scribed "X" B.T. both trees posted by Art 1968 a location poster on 10" Pine B.T.and an attention poster on 12" Fir 6 ft. from corner.
- 3. Painted corner monument and bearing trees with bright red paint.



1	Jack H. Ninneman
·	certify the information shown hereby is touc and course.
10" PINE ANRES	Signature Cree of Party Chief Jack H. Ninneman
POSTER TLAS PATTACHED	certify that this Corner Record correctly tag machine which performed by me or under by direction in compliance with the "Corner Recordation Act" (70-22-101, at seq., 71.D.A.)
8"PINE	Signature of Surveyor & Feel 9/25/81 46615 Date:
SKETCH OF CORNER	Employer: Ninneman Engineering Inc.
Office of Clerk and Recorder, County of Lincoln	Sec. 25
record" was filed for record on the November 5th	day of 1987
was noted on the cross-index plat and is assigned page No. <u>133</u>	55 in
	In By Betty L. Concar
Cross Index No. 4-25 T	26N R. 30W PMM e - corner this sheet

CERTIFICATION