INSTRUCTIONS

 Original and/or s psequence record used to evaluate the corner on Wan

Description of evidence found, note discrepancies in the record, six a method of establishing los

- 2. Description of evidence found, note discrepancies in the record, was internol of evidence corners.

 3. Description of monument and accessories set to perpetuate the corner position.

 4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, luppgraphy ties, position of accessories, etc.


 5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.

 6. Fin in Cross India & Santon Diagram at bottom of short
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner NE Corner Section 34	T. 26N	R. 30W .	P.M.M. Linco	Ounty
-----------------------------	--------	----------	--------------	-------

- 1. 80 chains: Set Limestone 24 X 12 X 10 inches, 18 inches in the ground for the Corner Section 26,27,34, and 35. Marked with 1 notch on the S. and 2 notches on the East edge; and raise a mound of stone, 2 foot base, l_2 feet high West of corner.
- 2. Found: BLM brass capped monument from which a 12" Lodgepole Pine bears S41°E 25.7 feet scribed T26N.,R.30W S 35 B.T. and posted. A 10" Lodgepole Pine bears S51°W 28.4 feet scribed T26N.,R.30W S 34 B.T. and posted. A 10" Lodgepole Pine bears N41°W 20.5 feet scribed T26N.,R.30W. S 27 B.T. and posted. A 10" Lodgepole Pine bears N41 E 20.5 feet scribed T26N., R.30W S 26 B.T. and posted.
- 3. Painted monument and accessories with bright red paint.



Found BLM brass capped monument marked as shown.

	CERTIFICATION	
10"LP.PINE SCRIBED & POSTED	I. certify the information shown hereia is true and correct.	
CEIBED FROMED JACKED	Signature Ground Party Chief	
FAU 8	1. Jack H. Ninneman certify that this Corner Record correctly reported to conseption of by one or under by direction in compliance with the "Corner Recordation Act" (70-22-10), et seq., M.D.A.) Josh H. Ninneman Signature of Surveyor & Sa. J.	
FOUND B.L.M. BRASS CAP MKD, AS SHOWN ABOVE		
5010	1 *	
AT 10"LP PINE SCRIP DE POSTED	Date: 9/16/81 Reg. No. 4661S	
SCRIBED & SKETCH OF CORNER	Employer: Ninneman Engineering Inc.	
Office of Clerk and Recorder, County of Lincoln	Sec. 34	
record" was filed for record on the LOesenber 7th	day of 198%	
was noted on the cross-index plat and is assigned page No.	32, in	
book No! Eleanor & Rughn by County Other	Cial Deputy	
Cross Index No. V-17	T. 26N R. 30W PMM • corns s sheet	