INSTRUCTIONS

- 1. Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or uniterated
- Orners,

 J. Description of monument and accessories set to perpetuate the corner position.

 J. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

 J. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.

 J. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner	_C-S	S-S 1/6	54 Wi	tness	cor.	Sec.34	T. <u>26</u> 1	N	_R	_30W	 	P.M.M	Lincol	ln	·	County
	1.	This o	corne	r not	previ	ously	set.									

2. Set: a 3" X 30" aluminum capped monument marked as shown below from which, A 10" Larch bears S 71°E 14.9 feet scribed C-S-S 1/64 S34B.T. and posted. A 12" Larch bears S 11°E 6.0 feet scribed C-S-S 1/64 S34B.T. and posted. A location poster on a 5" Larch bears S 50°E 9.4 feet. Painted monument and accessories with bright red paint.

Set 3" aluminum monument marked as shown.

AND ALDER	
SET AN ALUMINUM MONUMENT 3"X 30" MARKED AS SHOWN. STIPE ID"LARCH FATON POSTER ON BT SKETCH OF CORNER 550°E 9.4 A.	CERTIFICATION Jeff Paullin certify the information shown herein is true and correct. Signature Grownd Party Chief Jack H. Ninneman certify that this Corner Record correctly represents work performed by me or under by direction in compilance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.) Signature of Surveyor & Sep. June 82 Reg. No. Employer: Ninneman Engineering Inc.
Office of Clerk and Recorder, County of Lincolu	Sec. 34
record" was filed for record on the	day of 1982
was noted on the cross-index plat and is assigned page No. $\frac{19}{2}$	
book No. Eleanor L. Vaush by B. Gounty Offici	ial deputy
Cross Index No. $\frac{Y/Z^{-1}S}{}$ T.	26N R. 30W PMM • - corner this sheet