INSTRUCTIONS

- Original and/or subsequent record used to evaluate the corm
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or onliterated
- Description of monument and accessories set to perpetuate the corner position.
 Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- Certification must be signed and scaled by Registered Land Surveyor in State of Montana.
 Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner SW-SE-SE 1/256 Cor. Sec. 34 T. 26N R. 30W P.M.M. Lincoln County

- 1. This corner not previously set.
- 2. Set: a 3" X 30" aluminum capped monument marked as shown below from which,
 A 12" Pine bears S 76 E 19.6 feet scribed SW-NE-SE 1/256 S34B.T. and posted.
 A 10" Larch bears S21 E 26.6 feet scribed SW-NE-SE 1/256 S34B.T. and posted.

 - A location poster on a 13" Pine bears S31°E 9.5 feet.
 - Painted monument and accessories with bright red paint.



Set 3" aluminum monument marked as shown.

SET AN ALUMINUM MONUMENT 3"x 30" MARKED AS SHOWN. S76°E 12"PINE 19.6FT BT	CERTIFICATION I David Stanley certly the information shown herein is true and correct. Signature Ground Party Chief Jack H. Ninneman certify that this Corner Record correctly represents work performed by me or under by direction in compilance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.) Signature of Surveyor & Scal
SKETCH OF CORNER BEARS 531°E 9.5 Ft. Office of Clerk and Recorder, County of Lincoln	Date: June '82 Reg. No. 4661S Employer: Ninneman Engineering Inc. Sec. 34 This "corner
record" was filed for record on the	day of 19/2
book No. <u>Eleanor L. Jaugher L.</u> County Office X V- 1/2 17	by Betty L. Conces deputy