

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

1/4 of Secs. 35 & 36

Corner _____ T. 26 N., R. 30 W., P.M.M. Lincoln County

- I. 1916 G.L.O. Original Record by S. Frank Walters: "Set a washed slate stone, 16x8x8 ins. 10 ins. in the ground, for 1/4 sec. cor., mkd. 1/4 on the W. face, from which,

A tamarack, 30 ins. diam., bears S11 1/4° E. 370 lks. dist., mkd. 1/4 S 36 BT.

A tamarack, 36 ins. diam., bears S7 1/4° W., 462 lks. dist., mkd. 1/4 S 35 BT."

1968 B.L.M. Remonumentation: "The 1/4 sec. cor. of secs. 35 and 36, as determined from the remains of the original SE bearing tree, falls in Silver Butte Creek, unsuitable for monumentation.

from which

The original bearing trees:

A snag, 30 ins diam., bears S11 1/4° E., 370 lks. dist., mkd. 1/4 S36 BT. (Record)

The new bearing trees:

A larch, 13 ins. diam., bears S24° E., 74 lks. dist., mkd. 1/4 S36 BT.

A larch, 20 ins. diam., bears S37° W., 19 lks. dist., mkd. 1/4 S35 BT."

- II. No original monument found, stone falls in old creek channel at a point established by distance - distance intersect of original bearing trees.


A larch snag, 30 ins. diam., bears S11 1/4° E., 244.3 ft. (370 lks.) dist., visible scribe (original).

A larch, 36 ins. diam., bears S7 1/4° W., 304.9 ft. (462 lks.) dist., overgrown scribe (original).

A larch, 17 ins. diam., bears S26° E., 52.4 ft. (79 lks.) dist., overgrown scribe (B.L.M. record S24° E. 74 lks.).

A larch, 27 ins. diam., bears S16° W., 11.7 ft. (18 lks.) dist., overgrown scribe (B.L.M. record S37° W. 19 lks.)

- III. At distance - distance intersect from the original bearing trees, set a 3/4 in. dia. by 30 ins. long, aluminum rod, 26 ins. in the ground with a 3 1/4 in. dia. aluminum cap marked as shown:



Painted red bands around the bearing trees and attached Bearing Tree and Land Survey Monument signs. Set a 6 ft. galvanized steel guard post with Land Survey Marker and Property Boundary decals, 4 ft. South.
Magnetic Declination: 20° 30' East



SKETCH OF CORNER

CERTIFICATION

1. Kenneth Kern
certify the information shown herein is true and correct.

Signature Ground Party Chief
1. Alvah F. Hughes
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

Signature of Surveyor & Seal

Date: 10/29/91 Reg. No. 7322


Employer: U.S. FOREST SERVICE

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on April 21, 1992 was noted on the cross-index plat and is assigned page No. 5000, in book No. _____

County Official

X-17 26 N 30 W
Cross Index No. _____ T. _____ R. _____ PMM

Sec. 35



• - corner this sheet