- INSTRUCTIONS

  1. Original and/or subsequent record used to evaluate the corner position.

  2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
- Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
   Description of monument and accessories set to perpetuate the corner position.
   Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
   Certification must be signed and scaled by Land Surveyor registered in the State of Montana.
   Fill in Cross Index & Section Diagram at bottom of sheet.

## **CERTIFIED CORNER RECORDATION**

Corn	er	T	26 N.,	_R	32 W.,	_ P.M.M	Sanders	County
· <u>1</u>	990 BLM records: BLM plat and records	not ap	proved at	this	date.			
m	ound a 2 1/2 ins. diam. iron pipe, 4 inarked as shown:	/	-E-NW-NE 1 S29 1990		n 3 1/4 ir	ns. diam.,	BLM brass cap,	
	A larch, 8 ins. diam., bears S44 W	hs 1	et diet	-/ 	C E ML N	IE 1/256 o		
	A larch, 9 ins. diam., bears N83 W							
M	agnetic declination: 20 East							
II. P	ainted red hands around the hearing to	000 0ná	i attoobod		Cumana M		al Barrelon Brown	

1

	Pranton Solater Of Survey
"LARCH NO3"W  51.5 FT.  NO SCALE.  8" LARCH SKETCH OF CORNER	CERTIFICATION  I. Kevin A. Todd certify the information shown herein is true and correct.  Signature Ground Party Chief  Ronald A. Pearson certify that this Corner Record correctly represents work perform by me or under my direction in compilance with the "Cor Baccardation Act" (70-22-101, et seq., M.C.A.)  Signature of Surveyor & Seal  12/17/92 Date: Reg. No.  Employer: U.S. FOREST SERVICE
Office of Clerk and Recorder, County of Lincohn record' was filed for record on 1-4-93 was noted on the cross-index plat and is assigned page No. book No. Coral M. Cum	Sec. 29  Sec. 29  5320  in  official  T. 26 N R. 32W PMM  • corner this she