INSTRUCTIONS

- 1. Original and/or subsequent record used to evaluate the corner position.
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- 3. Description of monument and accessories set to perpetuate the corner position
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

 6. Fill in Cross Index & Section Diagram at bottom of sheet.

Magnetic declination: 20° East

CERTIFIED CORNER RE	CORDATION
---------------------	-----------

C-S-N-NE 1/256 S29 32 W.,__ P.M.M. Sanders Corner . County 1990 BLM records: BLM plat and records not approved at this date. Found a 2 1/2 ins. diam. iron pipe, 8 ins. below road surface, with 3 1/4 ins. diam., BLM brass cap, marked as shown: C-S-N-NE 1/256 \$29 1990 From which: A fir, 12 ins. diam., bears N24°E, 50.5 ft. dist., mkd. C-S-N-NE 1/256 S29 BT. A larch, 12 ins. diam., bears N88°E, 41.5 ft. dist., mkd. C-S-N-NE 1/256 S29 BT.

III. Painted red bands around the bearing trees and attached Land Survey Monument and Bearing Tree signs.



corner this sheet

12" FIR CERTIFICATION Kevin A. Todd certify the information shown herein is true Ronald A. Pearson certify that this Corner Record correctly represents work performed by me or under my direction in compilance with the "Corner No SCALE 12/17/92 9008LS _Reg. No. . U.S. FOREST SERVICE Employer: **SKETCH OF CORNER** Sec. 29 Office of Clerk and Recorder, County of . This "corner record" was filed for record on _ was noted on the cross-index plat and is assigned page No. Cosal M Cumaurgo.

County Official book No. .

26 N R. 32W

.75R-8

Cross Index No. -