## INSTRUCTIONS

- Original and/or subsequent record used to evaluate the corner
- 2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- Description of monument and accessories set to perpetuate the corner position.
- 4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

  5. Certification must be signed and scaled by Land Surveyor registered in the State of Montana.

  6. Fill in Cross Index & Section Diagram at bottom of sheet.

V4 CERTIFIED CORNER RECORDATION	
CornerS 33 •	T. <u>27 N</u> R. <u>27 W</u> P.M.M. <u>LINCOLN</u> Count
ORIGINAL AND/OR SUBSEQUENT RECORD	ORIGINAL RECORD: Set a Granite Stone, 18"x 12"x 6", 13" in the ground, marked 14 on W face;
	From Which: A Fir 10" in diam. bears N20°E, 151Ks. dist. marked 14 5 34 B.T. A Fir 10" in diam. bears N75°W, 24 lks. dist. marked 14 5 33 B.T.

EVIDENCE FOUND Found Set Stone with 1/4 on South Face. Found Rotted remains of the Original NE BT.

Left Stone in Place. Set 5' Steel Fence Post 2' North of Monument. **PERPETUATION** Established Two RM's. A 10" D. Fir bears 558°W, 21.2' and a 19" D. Fir bears 58°E, 7.1'. Both RM Trees, Blazed, Painted, Tagged with MARLS Land Monument Sign, and Scribed with R/M.

Note: Declination used - 20°E Measurements taken to center of Tree.

