- Original and/or subsequent record used to evaluate the corner position.
   Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated
- 3. Description of monument and accessories set to perpetuate the corner position.

  4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.

  5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.

  6. Fill in Cross Index & Section Diagram at bottom of sheet.

From Which:

u. 524°	CERTIFIED CORNER RECORDATION
Corner	T. 27 N R. 28 W P.M.M. LINCOLN County
ORIGINAL AND/OR SUBSEQUENT RECORD	ORIGINAL RECORD: Set a Lime Stone, 15" x 12" x 10", 10" in the ground, marked 1/4 on N face;

A pine 10" in diam, bears N 65° 45' E, 96 1Ks. dist. marked 14 524 B.T. A tamarack 10" in diam. bears 522° 30'E, 32 lks. dist. marked 14 525 B.T.

EVIDENCE FOUND Found Original Stone with 14 visable. From Which a 22" Tamarack bears 520°E, 21.0'. A original BT Dead + Down bears N 64°E, 63'.

PERPETUATION Left Stone in Place. Set 5' Steel Fence Post at approximately 1' South of monument. Established New RM Tree, An 12" Tamarack bears N50°E, 47.3 ! Placed MARLS Land Monument sign and Painted Red Band around original BT and new RM Tree.

Note: Declination used - 20° E

Measurements taken to center of tree

