INCTOLICTIONS

- Original and/or subsequent record used to evaluate the corner position.
- Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
- 3. Description of monument and accessories set to perpetuate the corner position.
- Sketch of corner, show all pertliment data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
- 5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
- 6. Fill in Cross Index & Section Diagram at bottom of sheet.

	516	SIST CERTIFIED CORNER RECORDATION						
Corner	521	522		T. <u>27 N</u>	_R. <u>28 W</u>	P.M.M	LINCOLN	County

ORIGINAL AND/OR SUBSEQUENT RECOR

SUBSEQUENT RECORD ORIGINAL RECORD: Set a Lime Stone 24", 15", 10", 18" in the ground, marked with 3 notches on 5 and 3 notches on E edges;

From Which:

A fin, 18" in diam. bears N60°30'E, 9 lks. dist. mkd. T27N R28W S15 B.T. A pine, 9" in diam. bears S55°15'E, 39 lks. dist. mkd. T27N R28W S22 B.T. A pine, 10" in diam. bears S67°45'W, 57 lks. dist. mkd. T27N R28W S21 B.T. A fir, 16" in diam. bears N43° W, 45 lks. dist. mkd. T27N R28W S16 B.T.

EVIDENCE FOUND

Found Original Stone. From Which A 24" D. Fir bears N 60°E, 6.0' with scribing visible. A 24" D. Fir bears N 43°W, 29.0' with scribing visible.

PERPETUATION

Left Stone in Place. Set 5' Steel Fence Post 1' West of Monument. Established Two RM Trees. A 14" P. Pine bears 585°W 26.8' A 20" P. Pine bears 556°E, 25.0'. Both RM Trees Blazed, Painted and Tagged with MARLS Land Monument Sign.

Note: Declination used - 18°E Measurements taken to center of tree.

