INSTRUCTIONS

int record used to evaluate the corner position Description of evidence found, note discrepancies in the record, state m.

3. Description of monument and accessories a

4. Skeich of corner, show all pertinent c uch can best topography ties, position of accessories, (*

bown in a sketch example, corner marking,

5. Certification must be algned and sealed by Land Surveyor 5. Fill in Cross Index & Section Diagram at bottom of sheet. veyor registered in the State of Montana, i

CERTIFIED CORNER RECORDATION

TION 28 T. 27 N R. 28 W P.M.M. LINCOLN

1.) 1902 GLO RECORD-A SIX INCH PINE SCRIBED 14 528 ON N. 1/4 533 ON S.

> FROM WHICH BEARS: AN 8 PINE NO3°E 28 LINKS SCRIBED" 14 528 BT" AN 8 PINE 540°W 14 LINKS SCRIBED "1/4533 BT

FOUND

A 10" BLOWN DOWN PINE W/SCRIBING VISIBLE ON TWO SIDES IN DEEP BLAZES. ON THE SOUTH SIDE "3" IS VISIBLE, ON THE NORTH SIDE " 14528" IS VISIBLE. J. NIELS LUMBER CO. LOCATION POSTER IS ATTACHED. ROOT CROWN HOLE AND ROOTS STILL ATTACHED TO TREE VISBLE,

FOR CORRECT CORNER POSITION - SET 5/8"x. 24" REBAR W/ORANGE CAP STAMPED GOACHER 7318-5" IN THE STUMP HOLE IN A COLLAR OF ROCK FROM WHICH BEARS; A 10" FIR NIGE 88.95" W/SNOWBLAZE FOOTBLAZE "BT" AN 8" LARCH SIGN 3.90" W/SNOW BLAZE FOOTBLAZE BT"

TAGS ATTACHED TO BOTH BTS RED & WHITE GUARD STAKE SET NEAR LACOR

SEE C. OF S. #1851

10"FIR CERTIFICATION' KICHARD G. GOACHER certify the information shown herein is true and correct. Signature Cround Party Chief KICHHENS G. GOACHER certify that this Corner flycoffd for polly represents work performed 8"LARCH SKETCH OF CORNER GOACHUR !

Office of Clerk and Recorder, County of Linesh This "corner			Sec. 28				
record" was filed for record on	ug 5, 1991				<u> </u>	<u> </u>	
was noted on the cross-index plat and	is assigned page No	1551	- n				
book No.	Coral Mounney		efsj				
	County Off	liciál .	·			·	

Adopted July 1, 1981, Montana Board of Professional Engineers & Land Surveyors

corner this sheet

I. ORIGINAL AND/OR SUBSEQUENT RECORD:

This item should describe or quote those portions of the original or subsequent record which were used in evaluating the corner position. The original record will usually be the General Land Office field notes. Subsequent record can come from several sources: Previously filed corner records, maps and plats, private and public records, etc. Some of the subsequent record, even though not in the public record, but known to have validity by the surveyor, may be quoted and appropriately noted.

The record data helps support the reestablished corner position because it clearly shows what history the surveyor based his corner position on. In some cases, however, the record may be unknown or not pertinent. A statement to that effect should appear on the corner record.

11. DESCRIPTION OF EVIDENCE FOUND OR METHOD OF LOCATING CORNER POSITION:

This item will describe the original or subsequent record evidence found. If portions of the found evidence cannot be reconciled with the record, then the disregarded record should be noted, and, if possible, an opinion as to its cause narrated.

If no physical evidence of the original or subsequent monuments and accessories can be found, then the method used to reestablish the lost or obliterated corner (single proportion, fence intersection, parol evidence, terrain calls, centerline of road, etc.) shall be indicated.

III. DESCRIPTION OF MONUMENTS AND ACCESSORIES SET TO PERPETUATE THE CORNER POSITION:

This item should list all details about the corner and its location which will help exclusively identify the corner position; including size and type of monument, how marked if not shown in sketch, and distinguishing topographic calls which help locate the corner. In many cases, instructions on how to find the corner should be included.

References or ties to other corners are optional and may be drawn on the face or back of the corner record form, or references to Certificate of Survey may be made. Separate drawings may be attached to the corner form.

If state plane coordinate values for the corner position are shown, then the control upon which they are based should be indicated.

IV. SKETCH OF CORNER:

This item will usually show how a found or set corner is marked and may also show topography or accessory monuments found or set and their relation to the corner. There is no stipulated format; the sketch could be transcribed field note entries.

V. CERTIFICATION:

The name and signature of the ground party chief is optional.

The Surveyor who performed or directed the field work which is depicted on the "Certified Corner Record" shall sign and affix his seal in the Certification.

The employer blank is optional but useful in tracking down original field note data or adjacent record if, in the future, questions arise about the corner.

. . .

The Cross Index at the bottom of the page should be completed by the Surveyor. Only the single Township Index where the corner is filled shall be completed.

The lower righthand corner is a corner location diagram and should have the pertinent section filled in at the top and a closed circle indicating the appropriate corner position in the section filled in. This is intended to be an aid in searching the "Record" once it has been filled.