

## INSTRUCTIONS


1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner  $\frac{1}{4}$  Cor. common to Sec. 29 & 32 T. 27 N. R. 29 W. P.M.M. Lincoln County

Original Record: Unknown

Subsequent Record: ( St. Regis Paper Co. ) Set:  $2\frac{1}{2}$ " I.P. 24" in the ground with a brass cap marked



DF. 6" N  $52\frac{1}{4}$  W 37 lks. S 29 New B.T.

Found: Monument and accessories as described above.

(See back of sheet)

## CERTIFICATION

I, James R. Short  
certify the information shown herein is true and correct.

James R. Short  
Signature Ground Party Chief

I, \_\_\_\_\_  
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.D.A.)

Signature of Surveyor & Seal

Date: \_\_\_\_\_ Reg. No. \_\_\_\_\_


Employer: Montana Dept. of Highways

## SKETCH OF CORNER

Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the March 14 day of 1984 was noted on the cross-index plat and is assigned page No. 2544, in book No. \_\_\_\_\_

James B. Siegel by Betty L. Coates  
County Official deputy

Sec. 32



Cross Index No. V - 7 T. 27 N R. 29 W P.M.M.

• - corner this sheet