

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Closing corner common to Sec. 6 and 7, T27N, R29W, MPM, found original stone loosely set and plainly marked (record - set a limestone, 15 x 12 x 8 ins., 10 ins. in ground for closing cor. of Secs. 6 and 7, marked CC on E., with 5 grooves on S. and 1 groove on N. faces;) from which:

A fir, 15 ins. diam, bears N. 64°E., 9 Lks. Dist. stump with scribing visible.
(Record - a fir, 12 ins. diam., bears N. 64° E., 9 Lks. Dist., marked T27N, R29W S 6 BT).

**DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:**

For the closing corner common to Sec. 6 and 7, T27N, R29W, MPM, Date of work: Oct. 15, 1971
I reset the original corner stone from record bearing and distance from original BT. from which:

A 5 in. Douglas fir bears N 44°E - 32 Lks. Dist. marked RM

A 7 in. larch bears S 47°E - 23 Lks. Dist. marked RM

I placed signs and paint on RM's and at corner

**SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)**

(Record from original G.L.O. field notes)

Surveyor's Seal

I, A. R. Trenkle and Joe French
certify that the information shown herein is true and correct.


A. R. Trenkle

Signature of Ground Party Chief

I, Stanley J. Skousen
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Stanley J. Skousen
Signature of Surveyor

DIAGRAM OF CORNER:



• = Corner recorded on the sheet

2532 - S
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 16th day of December 1971, was noted on the cross-index plat and is assigned page No. 239, in book No. 1

Edward L. Clough Deputy
County Official
Cross Index No. E3 T. 27 N. R. 29 W. Mer.