

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch or corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Registered Land Surveyor in State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner Southwest Section 10 T. 27N R. 29W P.M.M. Lincoln County

Record 1911

Set a limestone, 14x12x6 ins. 10 ins. in the ground, for closing corner of sections 10 & 15, marked CC on East face, with 2 grooves on North and 4 grooves on South face; from which:

A Fir 16 ins. diam. bears N 51 E 20 lks. marked T27N R29W S 10
B T

A Fir 14 ins. diam. bears S 44 E 1 lks. marked T27N R29W S 15
B T

Remonumented B.L.M. 1966

Set iron post 30 ins. long 2½ ins. diam. 24 ins. into the ground from which:

The original bearing trees:

A Fir 16 ins. diam. bears S 44 E 56 lks marked T27N R29W S15 BT
(record: S 44 E 60 lks.)

The new bearing tree:

A Larch 18 ins. diam. bears N 13½ E 57 lks. marked CC T27N R29W S 10 BT

Buried original stone along side the iron post.


Found

3¼ inch B.L.M. brass cap, from which;

A 20 inch larch bears N 11 E 36.80 feet, marked T27N R29W S10 BT

A 20 inch fir bears S 44 E 34.60 feet, with scribe overgrown

Maintained BTs with required signs and paint. Set a U.S.D.A. steel post 3 feet north.



SKETCH OF CORNER

CERTIFICATION

I, Dan Croft

certify the information shown herein is true and correct.

GENE WARREN
Signature Ground Party Chief

I, GENE WARREN
certify that this Corner Record correctly represents work performed by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101 et seq., M.C.A.)

2734 S
Signature Registered Professional Surveyor

2734 S
Signature Registered Professional Surveyor

Date: 8/17/89

Employer: ROCKY MOUNT SURVEYORS


Office of Clerk and Recorder, County of Lincoln. This "corner record" was filed for record on the Aug 16 day of 1989 was noted on the cross-index plat and is assigned page No. 4070, in book No. _____

Janet E. Siegel by Bill Snickhoff
County Official

Cross Index No. 1-13

T. 27N R. 29W P.M.M.

Sec. 10



• - corner this sheet