CERTIFIED LAND CORNER RECORDATION

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

W 1/16 Corner Section 17 Twp. 27 N., R. 29 W. P.M.M. Not previously set.

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 12/18/80

T. 27N R 29W Mer.

Set a 5/8" X 24" capped steel pin (stamped J.H.N. 4661S) from which a 36" Cottonwood bears N $57^{\circ}E$ 12.6 feet. Scribed W 1/16 S 17 B.T. and posted.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)			
] }	TWP. 27N., R	29W. P.M.M.
7 8 FND. B.L.M.B.C.	W 16 SET 58 X24"	N89°47'08'W	
18 17 A B.T. 5 (3) 7.69	73/7.69	COMPUTED	4B.T.S 17 16
	D (DIAGRAM OF CORNER:
Surveyor's Seal	Surveyor's Seal I, DAVID STANLEY certify that the information shown herein is true and correct. Signature of Ground Party Chief I, JACK H. NOVETA certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.		N.
Marine Constitution of the			SEE SKETCH
The state of the s	Jack H. Ring Signature	of Surveyor	= Corner recorded on the sheet
		466/5 Registration Number	:

This "corner record" was filed for record on the 29th day of January 1981, was noted on the cross-index plat and is

Cross Index No.

J-9

Office of Clerk and Recorder, County of.....

3 Form 125—7887

assigned page No. 973 in book No.