

## INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, note discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

## CERTIFIED CORNER RECORDATION

Corner SW 1/16 S12 T. 27 N. R. 30 W P.M.M. Lincoln County

## Record:

1993 Corner Monumentation.

Set a standard Forest Service 3 1/4" Aluminum cap, stamped T. 27 N, R 30 W, SW1/16, S12, RLS9958, 1993, on a 30" X 3/4" aluminum shaft 26" in the ground with a mound of stone, from which;

A 13" larch bears N .12° W., 41.9 feet dist., scribed SW1/16 S12 BT.

A 15" Douglas fir bears N.90°E., 11.2 feet dist., scribed SW1/16 S12 BT

A 6' steel post with Land Survey Monument decal attached bears NL'Y, 1 ft.

Corner falls on steep moderately treed SWLY slope

## Found:

Standard Forest Service 3 1/4" Aluminum cap stamped as shown below.

In the ground with a mound of stone, from which

A 16" larch bears N. 02° W., 42.6 feet dist., scribed SW1/16 S12 BT

A 17" Douglas fir bears S 85°E 11.7 feet dist., scribed SW1/16 S12 BT.

A steel post with Forest Service Boundary decal bears S. 85°W. 6 feet dist. and

A steel post with Forest Service Boundary decal bears S.0 °E. 5.6 feet dist.

Bearings by Silva compass 20° E. Decl.  
Distance by fiberglass tape

Fnd. steel post W/Forest  
Service Boundary decal

FND.  
3 1/4" ALUMINUM CAP  
MARKED

Fnd. 16" larch

Fnd. 17" fir

Fnd. steel post W/Forest  
Service Boundary decal

FND.  
3 1/4" ALUMINUM CAP  
MARKED

T 27 N R 30 W

SW 1/16

S 12

RLS 9958

1993

## CERTIFICATION

I, Darrell Vermilyea  
certify the information shown herein is true and correct.

Signature of Ground Party Chief

I, Donald M Roeder  
certify that this Corner Record correctly represents work  
performed by me or under my direction in compliance with  
the "Corner Recordation Act" (70-22-101 et seq., MCA)

Signature of Surveyor & Seal

Date: 8/28/01

Reg No: 10999LS

Employer: MDT


## SKETCH OF CORNER

Office of Clerk and Recorder, County of Lincoln. This "corner  
record" was filed for record on 12/3/2001  
was noted on the cross-index plat, and is assigned Page No. 1054

Coral M Cummings By RB

County Official

Sec. 12



• — Corner this sheet

Cross Index No. H-22 T. 27 N R. 30 W, PMM