

CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSH 5681.65)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

The original corner post and the small 3" BT in Section 12 were not found. The Section 1 BT is a dead Larch, 14" dbh, with scribing

Original record:

Set post 3' long, 3" sq. from which,
Pine 3" South 5 lks
Tam. 12" N 20°W 127 lks

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 11/20/69

Set a 4" square post at GLO bearing and distance from the Sec. 1 BT from which a

LPP, 4" dbh, scribed BT, N 42°15'E, 15 lks.

LPP, 3" dbh, scribed BT, S 22°30'E, 6 lks.

Rock mound erected around corner post; metal tags affixed to BT's.

The corner is about 125' south of a logging road.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

Surveyor's Seal

I, _____
certify that the information shown herein is true and correct.

Signature of Ground Party Chief

I, Robert F. Burdick
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Robert F. Burdick
Signature of Surveyor

DIAGRAM OF CORNER:

N.

Sec. 1

Sec. 12

T. 27N., R. 30W.

◆ = Corner recorded on the sheet

1495
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 19th. day of January 19 70, was noted on the cross-index plat and is

assigned page No. 162, in book No. 1

ELEANOR L. VAUGHN, By: Mae Watson
County Official Deputy.

Cross Index No. E-23 T. 27 R. 30 Mer.