CERTIFIED LAND CORNER RECORDATION

(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found original wooden post lying on ground, plainly marked, and found rotted remains of original wooden post underground. (Record - A fir post 5 ft. long, 6 ins. square, set 2 Ft. in ground, with mound of earth scribed N.B. 3-10571) found N.W. Loc. Cor., A. 18" cedar, alive and blazed bears N35 W-31 Ft. distance (Record - the N.W. Loc. Cor. bears N35°52'W - 31 Ft.

Found a Lch. 18" in Dia. $N69\frac{1}{2}$ °W. -14.4 Ft. Dist. - Marked BT NB 3 10571

(Record - None)

Found a Lch. 19" in Dia. S 6½°W - 5.6 Ft. Dist. - Marked BT NB 3 10571 (Record - None)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

For Cor. No. 3, "Northern Bell Lode" MS No. 10571 I set a 2 in. galvanized iron pipe 24 inches in ground, with brass cap marked. I set the iron post in the exact center of the rotted remains of the original wooden post.

SJS **1**532 S 3 NB 10571 1970

The original BT's were found alive and in good condition. I placed signs and paint on BT's and at corner.

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY. (MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original field notes)

Surveyor's S	eal
--------------	-----

a.R. Trenkle

Signature of Ground Party Chief

I, Stanley J. Skousen
certify that I have carefully performed or reviewed the
work done on the diagrammed corner as reported on this
recordation form and approve the same.

Signature of Surveyor

= Corner recorded on the sheet

DIAGRAM OF CORNER:

N. T 27N R 30W

3 NB

MS 10571

2532 S

Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 20th. day of April 19.71, was noted on the cross-index plat and is assigned page No. 215, in book No. 1

ELEANOR L. VAUGHN, By: Malwallow

County Official Deputy

Cross Index No. 0-2. T. 27 R. 30 Mer.