

INSTRUCTIONS

1. Original and/or subsequent record used to evaluate the corner position.
2. Description of evidence found, not discrepancies in the record, state method of establishing lost or obliterated corners.
3. Description of monument and accessories set to perpetuate the corner position.
4. Sketch of corner, show all pertinent data which can best be shown in a sketch example, corner marking, topography ties, position of accessories, etc.
5. Certification must be signed and sealed by Land Surveyor registered in the State of Montana.
6. Fill in Cross Index & Section Diagram at bottom of sheet.

CERTIFIED CORNER RECORDATION

Corner 1/4 S1/S12 T. 27N R. 30W P.M.M. Lincoln County

RECORD:

1900 - GLO Survey by Burton S. Adams

Set a limestone, 16 x 8 x 4 ins., 11 ins. in the ground for 1/4 sec. cor., marked 1/4 on N. face, from which

A fir, 9 ins. diam., bears N33° 30 feet E., 19 lks. dist., marked 1/4 S1 BT.
A fir, 8 ins. diam., bears S37° 45 feet E., 20 lks. dist., marked 1/4 S12 BT

FOUND:

Nothing.

PERPETUATION:

The new corner position was established as a result of a subdivisional survey of Section 12. Said subdivisional survey was made in accordance with methods and procedures contained in the Manual of Surveying Instruction; U.S. Bureau of Land Management.

Set a standard Forest Service 30" Aluminum monument, stamped as shown below, 18" in the ground with a large mound of stone around the monument, From which;

A 4" ponderosa pine bears N10°E, 11.3 feet dist., scribed BT and blazed with an X.
A 6' steel post with Land Survey Monument sign and location tag attached, bears S25°E, 3.8 feet dist.

A second 6' steel post with Land Survey Monument sign and location tag attached bears N33°W, 5.4 feet dist. No other trees of reasonable size were within 200' feet to be used as BT's.

T27N R30W
S1
1/4-----
S12
RLS 9958
1993

S 1

6' post @ 4" ponderosa Pine
BT
6' post

S 12

SKETCH OF CORNER

CERTIFICATION

I, John Marquette

certify the information shown herein is true and correct.

Signature Ground Party Chief


I, JAMES R. STAPLES

certify that this corner Record correctly represents work done by me or under my direction in compliance with the "Corner Recordation Act" (70-22-101, et seq., M.C.A.)

Signature of Surveyor & Seal

Date: 12-20-93 Reg. No. 9958LS

Employer: T.R.S. SURVEYING INC.



Sec. 12

Office of Clerk and Recorder, County of LINCOLN. This "corner record" was filed for record on 12-23-93 was noted on the cross-index plat and is assigned page No. 6065 in book No. _____

Carol M. Cummings by 1616
County Official

Cross Index No. A-13 T. 27N R. 30W PMM