

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found rotted remains of original corner post in hole. (Record-set a fir post, 8 ins. square, 4 ft. long, 1½ ft. deep; scribed 3-8797.) from which:

A hemlock 36 in. diam. bears N 43°E - 10.8 Ft. alive with all scribing visible.
(Record - A blazed hemlock tree, 2½ Ft. Diam., scribed B.T. 3-8797, bears N 43°E, 10.8 Ft.)

A hemlock 30 in. diam. bears S 42°30'W - 23.3 ft. alive with all scribing visible.
(Record - A blazed hemlock tree, 20 ins. dia., scribed B.T. 3-8797, bears S 42°30'W, 23.3 ft.)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 11/3/70

For corner No. 3 "Johnstone Placer" MS 8797
I set a 2 in. galvanized iron pipe 24 inches in the ground at
the exact center point of the original wooden post, with brass cap marked

I placed signs and paint on BT's and at corner

SJS 2532 S

8797
JP 3
1970

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original field notes)

Surveyor's Seal

I, A. R. Trenkle and Harold Etienne
certify that the information shown herein is true and correct.

A. R. Trenkle
Signature of Ground Party Chief

I, Stanley J. Skousen
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Stanley J. Skousen
Signature of Surveyor

2532 -S
Registration Number

DIAGRAM OF CORNER:

N. T 27N R31W
JP 3
MS 8797

= Corner recorded on the sheet

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 20th. day of April 1971, was noted on the cross-index plat and is assigned page No. 216, in book No. 1

ELEANOR L. VAUGHN, By: Mae Watson
County Official Deputy

Cross Index No. L-15 T. 27 R. 31 Mer.