

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

No physical evidence of the original corner post or mound was found. (Record - A tamarack post, 4 ft. long, 4 ins. square set 2 ft. in ground, with mound of stone, scribed M. 1-8995.) from which:

A larch 18 in. diam. bears North-25.9 ft., snag with all scribing visible.
(Record - A blazed tamarack tree 17 ins. in diam. scribed B.T.M. 1-8995 bears North - 25.9 ft.)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 11/5/70

For Cor. No. 1 "Mascott Placer" MS 8995

I set a 2 in. galvanized iron pipe 24 inches in the ground, with
brass cap marked.

SJS 2532 S

I set corner from the original BT., from which:
A white pine 9 in. diam. bears S47°W - 10.5 ft., marked RM

1
M
8995

A spruce-10 in. diam. bears N 1°E - 7.7 ft. marked RM
I placed signs and paint on BT's and at corner

1970

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original field notes)

Surveyor's Seal

I, A. R. Trenkle and Harold Etienne
certify that the information shown herein is true and
correct.

A. R. Trenkle

Signature of Ground Party Chief

I, Stanley J. Skousen
certify that I have carefully performed or reviewed the
work done on the diagrammed corner as reported on this
recording form and approve the same.

Stanley J. Skousen
Signature of Surveyor

DIAGRAM OF CORNER:

N. T27N R31W

1
M
MS 8995

= Corner recorded on the sheet

2532 -S
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 20th day of April 1971, was noted on the cross-index plat and is
assigned page No. 222, in book No. 1

Eleanor L. Hughes, Esq. Mae Watson
County Official Deputy

Cross Index No. E-F-21-32 T. 27 R. 31 Mer.