

CERTIFIED LAND CORNER RECORDATION
(REFERENCE FSM 7153.53)

DESCRIPTION OF CORNER EVIDENCE FOUND, AND ORIGINAL RECORD (IF KNOWN)

Found original corner post lying on ground plainly marked (Record - A tamarack post 4 ft. long, 4 ins. sq. set 2 ft. in ground with a mound of earth, scribed Y.J. No. 2, 3-8995.) from which:

A larch 13 in. diam. bears S 45°E - 3.8 ft., snag with all scribing visible.
(Record - A blazed tamarack tree 10 ins. diam. scribed B.T.Y.J. No. 2, 3-8995, bears S 45°E - 3.8 Ft.)

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED
TO PERPETUATE THE ORIGINAL LOCATION OF THIS CORNER:

Date of work: 11/5/70

For cor. No. 3 "Yellow Jacket No. 2 Placer" MS 8995
I set a 2 in. galvanized iron pipe 24 inches in the ground
with brass cap marked
I set corner from original BT., from which:

YJ 2
8995
3

A cedar 14 in. diam. bears S 14°W - 34.2 Ft., marked RM

I placed signs and paint on BT and at corner.

SJS 2532 S

1970

SKETCH, WITH COURSE AND DISTANCE TO ADJACENT CORNERS IF DETERMINED IN THIS SURVEY.
(MAY SKETCH OR PASTE REPRODUCTION ON REVERSE SIDE.)

(Record from original field notes)

Surveyor's Seal

I, A. R. Trenkle and Harold Etienne
certify that the information shown herein is true and correct.

A. R. Trenkle

Signature of Ground Party Chief

I, Stanley J. Skousen
certify that I have carefully performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve the same.

Stanley J. Skousen

Signature of Surveyor

DIAGRAM OF CORNER:

N. T 27N R31W

↑ YJ 2
3

MS 8995

= Corner recorded on the sheet

2532-S
Registration Number

Office of Clerk and Recorder, County of Lincoln

This "corner record" was filed for record on the 20th day of April 1971, was noted on the cross-index plat and is assigned page No. 223, in book No. 1

Eleanor L. Vaughn By: Mar. Waters
County Official Deputy

Cross Index No. 21 T. 27 R. 31 Mer.